

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8731-32)

Set a Pine post, 4 ft. long, 4" sq., 20" in the ground marked ¼ S on N. face for the ¼ Sec. cor., from which
A Pine 30" dia., bears S.12°W., 61 lks. dist. mkd. ¼ S BT.
A Pine 36" dia., bears N.65°W., 42 lks. dist. mkd. ¼ S BT.

Reported as not fd, Fd. Squared post & tagged trees, not scribed - by Roseburg Lmbr Co. No OBTs fd. 3/1970 C.S. File 54/36-106 - (added 10/12/2016)

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1086, surveyed April/June 1982 - (DCSO records Vol. 46 Page(s) 17562)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked T 32 S R 7 W
¼ $\frac{S \ 2}{S \ 11}$
1982

from which
A Fir 8" dia., bears N.32½°E., 22 lks. dist. mkd. ¼ S2 BT.
A Fir 8" dia., bears S.80½°W., 39½ lks. dist. mkd. ¼ S11 BT.