

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION S C for Secs. 35 and 36 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8701)

Set a Yew post 4½ ft. long 4" sq., 20" in the ground, for standard cor. to secs. 35 and 36, marked S C T32S R7W on N.; S36 on E.; and S35 on W.; one notch on E. and 5 on W., from which

- A Fir 24" dia., bears N.30°E., 14 lks. dist. mkd. S C T32S R7W S36 BT.
- A Fir 14" dia., bears N.46°W., 37 lks. dist., mkd. S C T32S R7W S35 BT.
- A Fir 6" dia., bears S.10°W., 23 lks. dist., mkd. S C T33S R7W S2 BT.

Survey by Milner L. Larson - For: Robert Dollar Co. - Dec. 21, 1967 - C.S. File 55/15-5

Found - Orig. 30" Fir stump, N.35°E., 10.0 ft., old hack marks outline face.
Orig. 16" Fir stump, N.47½°W., 24.0 ft., only root collar remains.
Orig. 28" Fir stump, S.7°E., 13.0 ft. bark scribing reads "BT"

Set 1¼" ID Iron pipe for the corner and scribed following BTs
16" D.Fir N.33°W., 17.5 ft.
12" D.Fir N.27°W., 15.0 ft.
17" Live Oak S.0°30'E., 32.0 ft.

All bearings were taken with a staff compass, Var. 19°00'E. Distances were measured with a steel tape.

BLM resurvey by John Jelley, Rollin Aanrud, and Lynn Roseberry, Cadastral Surveyors, under Group #'s 350 and 688, surveyed May 1969/March 1970 (DCSO records Vol. 35 Page(s) 14470-71)

The original standard cor., perpetuated and recorded by Larson in 1967, monumented with an iron pipe, 1¼" dia., firmly set, projecting 2" above ground, from which the original bearing trees:

- A sawed Fir stump 30" dia., bears N.30°E., 14 lks. dist. with no marks visible.
- A sawed Fir stump 32" dia., bears S.10°E., 19 lks. dist., with opened and rotted blaze. There are illegible scribe marks visible on bark blaze alongside rotted blaze. (Rec. S.10°W., 23 lks.)

(Cont. Next Page)

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION S C for Secs. 35 and 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

The rotted remains of a Fir stump, size indeterminate, bears N.46°W., 37 lks. dist., with no marks visible. and bearing trees mkd. by Larson

A Fir 15" dia., bears N.32°E., 23 lks. dist., with healed blaze.

A Live Oak 17" dia., bears S.1°E., 48½ lks. dist., with scribe marks 3642 BT visible on open blaze.

A Fir 18" dia., bears N.33°W., 27 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked S C

T 32 S R 7 W

S 35 | S 36

1969

Insert iron pipe inside iron post.

Cor. Fd. and Used in BLM survey by Roseberry and Aanrud, under Group #845, surveyed April/Nov. 1975 (DCSO records. Vol. 41 Page 16267)

James McIntosh - For: State of Oregon, Dept. of Forestry - June 2001 - M 138-51

Found - BLM brass cap, 1969 (in place)
24" Fir (1881) N.30°E., 14 lks. (now 21"x1' high rotted remains in place, no marks visible)
6" Fir (1881) S.10°E., 23 lks. (now 27"x2' high stump S.4°E., 13.4' rotted face exposed no marks visible.
16" Fir (1967) N.33°W., 17.5' (now 26" in place, face closed BT tag.)
12" Fir (1967) N.27°W., 15.0' (now 25" N.28°E., 13.8' face closed BT tag)
17" Live Oak (1967) S.00°30'E., 32.0' (now 21" in place, face closed) BLM BT tag.

Rewitnessed -

WP (Orange carsonite marker CBM-250 labeled witness post) N.08°W., 4.0' to base.

WP (Orange carsonite marker CBM-250 labeled witness post) N.75°E., 3.5' to base.

continued next page

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION S.C. for Secs. 35 and 36 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Stephan L. Barott, Cadastral Surveyor (Forest Service, USDA) under Group #1995, surveyed April/Nov. 2002 - (DCSO records Vol. 54 Page(s) 21154-5)

The standard cor. of secs. 35 & 36, on the S. bdy. of the Tp., monumented with an iron post, 2½" dia., firmly set, projecting 2" above the ground, with brass cap (properly) mkd from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears N.36½°E., 10.4 ft., with no scribe marks visible. (Record, N.30°E., 9.2 ft.)

A decayed fir stump, 26" dia., bears S.10°E., 13.4 ft., with no scribe marks visible. (Record, 12.5 ft.)

and BTs mkd. by Larson, reported by Roseberry & Aanrud

A fir, 25" dia., bears N.28°E., 15.2 ft. with a healed blaze. (Record, N.32°E.)

A live oak, 20" dia., bears S.1°E., 32.0 ft., with a healed blaze.

A fir, 26" dia., bears N.33°W., 17.8 ft., with a healed blaze.

Fd. BC & BTs by R. Wytcherly, 4/2008 - M156-10

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 8/2014 - C.S.
File 65/86-10

Condition report only

Found - BLM brass cap
26" Fir N.28°E., 15.2 ft. good scar.
21" Oak S.1°E., 32.0 ft. good scar.
27" Fir N.33°W., 17.5 ft. good scar.
W.P. N.75°E., 3.5 ft.
W.P. N.8°W., 4.0 ft.

Note - Compass decl. 15½°E.