

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

| | | | |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8713)

Set a Cedar post, 4 ft. long, 4" sq., 18" in the ground for corner to sections 25, 26, 35 and 36, mkd. T32S R7W S25 on NE. side, S36 on SE. side, S35 on SW. side, S26 on NW. side, with one notch on S. and E. edges, from which

- A Pine 15" dia., bears N.45°E., 50 lks. dist., mkd. T32S R7W S25 BT.
- A Fir 18" dia., bears S.5°E., 51 lks. dist., mkd. T32S R7W S36 BT.
- A Fir 16" dia., bears S.6°W., 55 lks. dist., mkd. T32S R7W S35 BT.
- A Fir 20" dia., bears N.20°W., 17 lks. dist., mkd. T32S R7W S26 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - March 6, 1968 - C.S. File 54/36-123

Found - Unrecorded I.Pipe at corner.

- Orig. 15" now 20" S.Pine, N.45°E., 33.0 ft., no marks visible.
- Orig. 20" now 38" D.Fir, N.15°W., (Rec. N.20°W) 11.2 ft., bark scribe visible, T32S R7W S26 BT
- Orig. 16" D.Fir, now down, S.6°W., 40.7 ft. (Rec. 36.3 ft.), bark scribe visible T32 and other mks
- Orig. 18" D.Fir, now down, S.5°E., 40.0 ft. (Rec. 33.7 ft.), marks visible.

Set Brass cap at cor. mkd: County Surveyors Office

| | | | | | |
|---|----|----|---|---|------|
| T | 32 | S | R | 7 | W |
| | S | 26 | | S | 25 |
| | S | 35 | | S | 36 |
| | | | | | 1968 |

- New BTs -14" D.Fir S.49½°E., 53.0 ft. mkd. T32S R7W S36 CSBT.
- 16" Laurel S.32°W., 77.5 ft. mkd. T32S R7W S35 CSBT.
- Reblaze and rescribe-
- 20" S.Pine N.45°E., 33.0 ft. mkd. T32S R7W S25 CSBT.

BLM Dependent resurvey by Stephan L. Barott, Cadastral Surveyor (Forest Service, USDA) under Group #1995, surveyed April/Nov. 2002 - (DCSO records Vol. 54 Page(s) 21155-6)

The cor. of secs. 25, 26, 35, & 36, perpetuated by the Douglas County Surveyor's Office in 1968, and recorded in C.S. file 54/36; monumented with an iron post, 1" dia., firmly set, projecting 7" above the ground, with brass cap (properly) mkd. continued next page

