

PRIMARY CORNER DESCRIPTION Sec Cor for 23, 24, 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8715)

Set a Fir post 4½ ft. long, 4" sq., 18" in the ground, for the cor. to secs. 23, 24, 25 and 26, marked T32S R7W S24 on NE.; S25 on SE.; S26 on SW.; and S23 on NW. also two notches on S. and one on E. angles of same, from which

A Fir 10" dia., bears N.18°E., 17 lks. dist., mkd. T32S R7W S24 BT.

A Fir 16" dia., bears S.45°E., 71 lks. dist., mkd. T32S R7W S25 BT.

A Laurel 12" dia., bears S.50°W., 22 lks. dist., mkd. T32S R7W S26 BT.

A Chinquapin 12" dia., bears N.3°W., 36 lks. dist., mkd. T32S R7W S23 BT.

Douglas Co. Surveyors Office - Vernon R. Tracy, J. Heritage, V. Perron, crew - March 11, 1970 - C.S. File 54/36-108

Found - Orig. 10" now 21" Fir, alive, N.18°E., 11.2 ft., shows good axe scar. We rescribe "T32S R7W S24 CS BT"

Orig. 16" now 30" Fir, alive, S.45°E., 46.9 ft., bark scribe visible, poor. Rescribe "T32S R7W S25 CS BT"

Set Brass cap at cor. mkd: County Surveyors Office

T 32 S R 7 W
S 23 | S 24
S 26 | S 25
1970

New BT - 40" D.Fir N.22°W., 42.9 ft. mkd. "T32S R7W S23 CS BT"

No suitable trees close in section 26.

This corner lies on very steep NE slope in scattered old growth Fir and dense Chinquapin and Laurel brush.

BLM resurvey by G. Steven Popken, Cadastral Surveyor & James J. Carlson, under Group #884. Surveyed Sept. 1975/June 1976 (DCSO records Vol. 37 Page(s) 15315-16)

The Sec. cor., perpetuated and recorded by Tracy in 1970, monumented with an iron pipe 1½" dia., firmly set, projecting 10" above ground, with 1970 brass cap from which the remains of the original bearing trees

A Fir 21" dia., bears N.21½°E., 17 lks. dist., with healed blaze. (Rec. N.18°E.)

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec Cor for 23, 24, 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 33" dia., bears S.48½°E., 71 lks. dist., with fragmentary scribe marks visible on bark and with healed blaze. (Rec. S.45°E.)
A Madrone root crown bears S.50°W., 18 lks. dist., no marks visible. (Rec. 22 lks.)
and a bearing tree mkd. by Tracy
A Fir 45" dia., bears N.22°W., 65 lks. dist., with scribe marks T32S R7W S23 CS BT visible on bark.
and a new bearing tree
A Chinquapin 7" dia., bears S.76¼°W., 37½ lks. dist., mkd. T32S R7W S26 BT.

FD. OK, by Mark Smalley, July 1993, M 117-43

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2925; Surveyed July/Dec. 2018 - (DCSO records Vol. 59 Page(s) 23771-2)

The cor. of secs. 23, 24, 25, and 26, reported by Popken and Carlson in 1975-76, monumented with an iron post, 1½" dia., firmly set, projecting 14" above the ground, with brass cap (properly) mkd.
from which the remains of BTs reported by Popken and Carlson
A fir, 33" dia., bears N.24½°E., 10.6 ft., with a healed blaze. (Original) (Record, N.21½°E., 11.2 ft.)
A sawed fir stump, 30" dia., bears S.48½°E., 46.2 ft., with a healed blaze. (Record, 46.9 ft.)
A fir, 44" dia., bears N.23¼°W., 41.9 ft., with a healed blaze. (Record, N.22°W., 42.9 ft.)
and a new bearing tree
A fir, 8" dia., bears S.64°E., 80.0 ft., mkd. T32S R7W S25 BT.
No suitable trees available in sec. 26.
NAD 1983 (2011)
Latitude: 42°46'03.67" N. Longitude: 123°29'15.17" W.