

PRIMARY CORNER DESCRIPTION Sec Cor for 13, 14, 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Pg 8717)

-----  
Set a Fir post 4 ft. long, 4" sq., 18" in the ground for the sec. cor. to 13, 14, 23 and 24, marked T32S R7W S13 on NE.; S24 on SE.; S23 on SW.; and S14 on NW. faces; also 3 notches on S. and one notch on E. angles, from which  
A Fir 6" dia. bears N.53°E., 17 lks marked T32S R7W S13 BT  
A Fir 5" dia. bears S.25°E., 38 lks marked T32S R7W S24 BT  
A Fir 40" dia bears S.88°W. 225 lks marked T32S R7W S23 BT  
A Fir 6" dia. bears N.20°W., 38 lks marked T32S R7W S14 BT

BLM resurvey by G. Steven Popken, Cadastral Surveyor & James J. Carlson, under Group #884. Surveyed Sept. 1975/June 1976 (DCSO records Vol. 37 Page(s) 15317)

-----  
Point for the cor. of secs. 13, 14, 23 & 24, at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked  
T 32 S R 7 W  
S 14 | S 13  
S 23 | S 24  
1976

from which  
A Fir 20" dia., bears N.33°E., 73 lks. dist., mkd. T32S R7W S13 BT.  
A Fir 17" dia., bears S.60½°E., 28 lks. dist., mkd. T32S R7W S24 BT.  
A Fir 8" dia., bears S.10°W., 58 lks. dist., mkd. T32S R7W S23 BT.  
A Fir 18" dia., bears N.29°W., 135 lks. dist., mkd. T32S R7W S14 BT.

Cor. Fd. and used in Corrective Dependent resurvey by Lynn Roseberry under Group #884, surveyed June 1979 (DCSO records, Vol. 41 Pages 16238-39)

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2925; Surveyed July/Dec. 2018 - (DCSO records Vol. 59 Page(s) 23773)

-----  
The cor. of secs. 13, 14, 23, and 24, reported by Roseberry in 1979, monumented with an iron post, 2½" dia., firmly set, projecting 8" above the ground, in a collar of stone, with brass cap (properly) mkd.  
from which bearing trees reported by Roseberry  
Continued next page

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 28" dia., bears N.33°E., 48.2 ft., with a healed blaze.  
A fir, 29" dia., bears S.60½°E., 18.5 ft., with a healed blaze.  
A fir, 15" dia., bears S.10°W., 37.7 ft., with a healed blaze. (Record 38.3 ft.)  
and a new bearing tree  
A fir, 7" dia., bears N.69½°W., 21.2 ft., mkd. T32S R7W S14 BT.