

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8719)

-----  
Set a Fir post 4 ft. long, 4" sq., 20" in the ground for the 1/4 S cor. mkd. 1/4 S on W. side, from which  
A Fir 10" dia., bears N.7°E., 13 lks. dist., mkd. 1/4 S BT  
A Laurel 6" dia., bears S.80°W., 12 lks. dist., mkd. 1/4 S BT.

BLM resurvey by G. Steven Popken, Cadastral Surveyor & James J. Carlson, under Group #884. Surveyed Sept. 1975/June 1976 (DCSO records Vol. 37 Page(s) 15318-19)

-----  
Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 16 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked  
T 32 S R 7 W  
1/4  
S 14 | S 13  
1976

from which  
A Pine 27" dia., bears S.78°E., 94 1/2 lks. dist., mkd. 1/4 S13 BT.  
A Cedar 7" dia., bears S.23 3/4°W., 46 lks. dist., mkd. 1/4 S14 BT.

Daniel Baker - For: Weyerhaeuser Co. - 12/2016 - M173-1

-----  
Found - 3 1/4" BLM brass cap "1976"  
31" pine, S.80°E., 62.3' to center, 1976 BLM BT (rec. S.78°E., 94 1/2 lks.)  
11" cedar, S.24°W., 30.6' to center, 1976 BLM BT (rec. S.23 3/4°W., 46 lks.)  
Marked - 13" cedar, N.48°E., 43.2' to nail side/center, scribed "1/4 S13 BT"  
17" pine, N.36°W., 74.3' to nail side/center, scribed "1/4 S14 BT"  
Note - 5 ft. metal post alongside corner.