

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8719)

 Set a Fir post, 4½ ft. long, 4" sq., 18" in the ground for the cor. to secs. 11, 12, 13 and 14, marked T32S R7W S12 on NE.; S13 on SE.; S14 on SW.; and S11 on NW. faces; also 4 notches on the S. and one on the E. angles of same, from which

A Cedar 12" dia., bears S.78°E., 26 lks. dist., mkd. T32S R7W S13 BT.

A Laurel 7" dia., bears S.45°W., 20 lks. dist., mkd. T32S R7W S14 BT.

A Fir 48" dia., bears N.82°W., 106 lks. dist., mkd. T32S R7W S11.

No tree convenient in Sec. 12.

Survey by Howard W. Johnstone - For: Roseburg Lumber Co. - Feb. 1970 - M 39-14

Found - One original bearing tree.

Set 5/8" Iron rod and alum. cap.

11" D.Fir N.59½°E., 18.8 ft.

16" D.Fir S.61°E., 4.1 ft.

20" D.Fir S.62°W., 3.1 ft.

16" D.Fir N.21°W., 27.2 ft.

BLM resurvey by G. Steven Popken, Cadastral Surveyor & James J. Carlson, under Group #884. Surveyed Sept. 1975/June 1976 (DCSO records Vol. 37 Page(s) 15319-20)

 The Sec. cor., perpetuated and recorded by Johnstone in 1970, monumented with a 5/8" iron rod, firmly set, projecting 6" above ground, with 1½" alum. cap mkd. T 32 S

11	12	R
14	13	7
		W

from which the remains of the original bearing trees

A Cedar 30" dia., bears S.66½°E., 26 lks. dist., with scribe marks T S visible on bark. (Rec. S.78°E.)

A madrone cluster bears S.60°W., 20 lks. dis., no marks visible.

and bearing trees mkd. by Johnstone

A Fir 11" dia., bears N.73°E., 28 lks. dist., with pitched over double blaze.

A Fir 18" dia., bears S.47½°E., 6½ lks. dist., with pitched over double blaze.

(Cont. Next Page)

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 20" dia., bears S.71°W., 4½ lks. dist., with pitched over double blaze.

A Fir 18" dia., bears N.11½°W., 41 lks. dist., with pitched over double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 32 S R 7 W
S 11 | S 12
S 14 | S 13
1976

Reset iron rod alongside iron post.

Fd. and used in BLM resurvey by Rogers and Bishop, under Group #1199, surveyed July 1984 (DCSO records, Vol. 47 Pages 17973-74)

Daniel Baker - For: Weyerhaeuser Co. - 12/2016 - M173-1

Found - 3¼" BLM brass cap "1976"
13" fir, N.60°E., 18.8' to center, 1976 BLM BT (BLM rec., N.73°E., 28 lks.) (rec. per M39-14 N.59½°E., 18.8')
29" fir, S.61°E., 3.9' to center, M39-14 BT (rec. M39-14 S.61°E., 4.1')
31" cedar, S.80°E., 17.2' to center, Orig. BT (BLM rec. S.66½°E., 26 lks) (rec. per 1881 GLO S.78°E., 26 lks.)
26" fir, S.63°W., 3.1' to center, 1976 BLM BT (BLM rec. S.71°W., 4½ lks) (rec. M39-14 S.62°W., 3.1')
24" fir, N.23°W., 27.2' to center, 1976 BLM BT (BLM rec. N.11½°W., 41 lks.) (rec. M39-14 N.21°W., 27.2 ft.)
Set - 5 ft. metal post alongside corner.
Note - 5/8" iron rod with 1½" alum. cap per M39-14 bears S.21°46'27"W., 0.16'