

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8721)

-----  
Set a Fir post, 4 ft. long, 4" sq., 22" in the ground for the corner to secs. 1, 2, 11 and 12, marked T32S R7W S1 on NE.; S12 on SE.; S11 on SW.; S2 on NW. and 5 notches on S. and 1 notch on E. angles of same, from which  
A Fir 30" dia., bears N.5°E., 12 lks. dist., mkd. T32S R7W S1 BT.  
A Fir 24" dia., bears S.50°E., 61 lks. dist., mkd. T32S R7W S12 BT.  
A Fir 30" dia., bears S.20°W., 100 lks. dist., mkd. T32S R7W S11 BT.  
A Fir 30" dia., bears N.40°W., 9 lks. dist., mkd. T32S R7W S2 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Cliff Stone, crew - Dec. 9, 1966 - C.S. File 54/36-87

-----  
Found - Orig. 30" now 36" Fir N.5°E., 7.9 ft., bark scribed, T32S R7W S1 BT  
Orig. 24" now 36" Fir S.50°E., 40.3 ft. barks scribed, T32S R7W BT  
Orig. 30" now 34" Fir S.20°W., 66.0 ft. bark scribed, T32S R7W S11 BT  
Orig. 30" now 36" Fir N.40°W., 5.9 ft. faint scribe marks visible.  
1" Iron pipe at sec. cor. (See Johnstone's survey M33-49)  
New BTs -9" D.Fir N.50°E., 11.6 ft. scribed T32S R7W S1 CS BT.  
7" D.Fir S.18°E., 27.2 ft. mkd. T32S R7W S12 CS BT  
9" Laurel S.35°W., 30.6 ft. mkd. T32S R7W S11 CS BT.  
This corner lies about 580.0 ft. West of ridge top. Location tag on top of ridge East of corner.

Fd. OK, March 1970 - DCSO JP C.S. File 54/36-106

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1086, surveyed April/June 1982 - (DCSO records Vol. 46 Page(s) 17561-62)

-----  
The Sec. cor., perpetuated by Johnstone in 1961 and recorded in 1969, and further perpetuated and recorded by Powell in 1966-67, monumented with an iron pipe 1" dia., firmly set, projecting 6" above ground, from which the remains of the original bearing trees (Cont. Next Page)

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A Fir 36" dia., bears N.5°E., 12 lks. dist., with scribe marks T32S R7W S1 BT visible on bark blaze.

A sawed Fir stump 48" dia., bears S.50°E., 61 lks. dist., with scribe marks R7W visible on bark blaze.

A Fir 34" dia., bears S.20°W., 96 lks. dist., with scribe marks T32S R7W S11 visible on bark blaze. (Rec. 100 lks.)

A sawed Fir stump 40" dia., bears N.40°W., 9 lks. dist., no marks visible.

and the remains of bearing trees mkd. by Powell

A Fir 10" dia., bears N.48½°E., 16 lks. dist., with healed double blaze.

A Fir 7" dia., bears S.15°E., 41 lks. dist., with healed double blaze.

A root hole bears S.35°W., 46 lks. dist., with a down madrone alongside 8" dia., with scribe marks 32S S11 CS visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 32 S R 7 W
S 2   S 1
S 11   S 12
1982

from which a new bearing tree

A Fir 7" dia., bears N.55°W., 47 lks. dist., mkd. T32S R7W S2 BT.

Reset iron pipe alongside iron post.