

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8723-24)

-----  
Marked a Laurel tree, 5" dia., ¼ S on W. side for ¼ sec. cor., from which  
A Laurel 6" dia., bears S.32°E., 12 lks. dist., mkd. ¼ S BT.  
A Fir 8" dia., bears S.5°W., 22 lks. dist., mkd. ¼ S BT.

Survey by Howard W. Johnstone - For: Roseburg Lumber Co. - Feb. 1969 - M 33-49

-----  
Found - Orig. 6" Laurel S.32°E., 7.9 ft., scribe visible.  
Orig. 8" D.Fir S.5°W., 19.0 ft., no scribe  
30" D.Fir S.11°E., 14.5 ft., scribe visible.  
(Assume orig. surv. took bear. to 8" D.F. and measured and scribed the 30" D.F.)  
Set 1" x 36" I.Pipe, and scribed  
20" D.Fir S.63°E., 48.1 ft.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1086, surveyed April/June 1982 - (DCSO records Vol. 46 Page(s) 17559-60)

-----  
The 1/4 sec. cor., perpetuated and recorded by Johnstone in 1969, monumented with an iron pipe 1" dia., firmly set, projecting 2" above ground from which the original bearing trees

A Madrone 18" dia., bears S.32°E., 12 lks. dist., with scribe marks ¼ visible on opened blaze.  
A Fir 32" dia., bears S.11°E., 22 lks. dist., with scribe marks ¼ S B visible on bark blaze. (Rec. S.5°W.)  
and a bearing tree mkd. by Johnstone  
A Fir 20" dia., bears S.63°E., 73 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.

At the corner point  
Set an aluminum post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked  
T 32 S R 7 W  
1/4  
S 2 S 1  
1982

from which a new bearing tree  
A Fir 13" dia., bears S.83½°W., 216 lks. dist., mkd. ¼ S2 BT.  
Reset iron pipe alongside iron post.