

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 13 and 24

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8718)

Set a Laurel post, 4 ft. long, 4" sq., 20" in ground, marked 1/4 S on N. side for 1/4 sec. cor., from which
 A Fir 10" dia., bears N.14°E., 17 lks. dist., mkd. 1/4 S BT
 A Laurel 6" dia., bears S.27°E., 28 lks. dist. mkd. 1/4 S BT

BLM resurvey by G. Steven Popken, Cadastral Surveyor & James J. Carlson, under Group #884. Surveyed Sept. 1975/June 1976 (DCSO records Vol. 37 Page(s) 15318)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
 Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 32 S R 7 W
 1/4 S 13
 S 24
 1976

from which
 A Fir 7" dia., bears North, 24 lks. dist., mkd. 1/4 S13 BT.
 A Fir 10" dia., bears S.13 1/2°W., 69 1/2 lks. dist., mkd. 1/4 S24 BT.

BLM Corrective Dependent Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #884 Surveyed, June 1979 - (DCSO records Vol. 41 Page(s) 16238)

Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

From this point, the 1/4 sec. cor., erroneously reestablished by Popken and Carlson in 1976, bears S.3°08'W., 0.18 chs. dist., monumented with an iron post, 2 1/2" dia., firmly set, projecting 4" above ground, mkd. and witnessed as described in the official record of the 1975-76 resurvey.

I remove the iron post, and at the true corner point
 Reset the iron post, 28" long, 2 1/2" dia., 23" in the ground, and in a mound of stone, 2 1/2 ft. base to top, with brass cap mkd.

T 32 S R 7 W
 1/4 S 13
 S 24
 1976
 1979

(Cont. Next Page)

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 13 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which bearing trees mkd. by Popken and Carlson
A Fir 8" dia., bears N.2½°W., 5 lks. dist., with scribe marks ¼ S13 BT visible on partially healed blaze.
A Fir 11" dia., bears S.10°W., 87 lks. dist., with scribe marks ¼ S24 BT visible on partially healed blaze.