

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8720)

-----  
Set a Cedar post, 4 ft. long, 4" sq., 22" in the ground for the 1/4 sec. cor., marked 1/4 S on N. face, from which  
A Laurel 6" dia., bears N.10°E., 47 lks. dist., mkd. 1/4 S BT.  
A Laurel 5" dia., bears S.7°W., 14 lks. dist., mkd. 1/4 S BT.

Survey by Howard W. Johnstone - For: Roseburg Lumber Co. - Feb. 1970 - M 39-14

-----  
Set corner at proportionate distance.  
Set 5/8" Iron rod and alum. cap.  
BTs - 9" D.Fir S.39 1/2°W., 19.3 ft.  
7" Chinquapin N.69 3/4°W., 12.2 ft.

David Edwards - Brant Miller, Party Chief & Eric Sprinkle, witness - Feb. 1, 2013 - C.S. File 65/78-6

-----  
Found - 5/8" dia., iron rod with aluminum cap.  
No trace of Johnstone's BTs  
New - A 6" dia., Fir scribed "T32S R7W S12 BT" bears N.32°W., 12.13 ft.  
An 8" dia., Fir scribed "T32S R7W S13 BT" bears S.82°E., 5.55 ft.  
Dec. 18°E