

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; and S. 36, T31-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16, 1881 (DCSO records Vol. 19 Page(s) 8024)

-----  
Set a Fir post 4 ft. long, 4" sq., for the ¼ sec. cor. 20" in the ground and marked ¼ S on N. side, from which  
A Laurel 5" dia., bears N.70°E., 20 lks. mkd. ¼ S BT.  
A Laurel 7" dia., bears S.60°W., 14 lks. mkd. ¼ S BT.

Survey by Howard W. Johnstone - For: Roseburg Lumber Co. - Feb. 1969 - M 33-49

-----  
Set 1½" x 24" I.Pipe by proportionate measurement.  
Scribed- 20" I.Cedar N.25°E., 34.5 ft.  
21" Y.Pine S.24°E., 28.2 ft.

Mark Smalley, L.S. #2354 - For: Kenneth Ford - July 1994 - M 120-43

-----  
Found - 1½" I.Pipe.  
30" Cedar N.25°E., 34.5 ft., healed.  
24" Pine, S.24°E., 28.2 ft., Part. healed.  
New BTs- 10" Fir, N.19°W., 13.7 ft., "¼ S BT"  
6" Fir, N.57°E., 18.6 ft., "¼ S BT"