

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (Tsp. cor.)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8631)

Bearing trees to closing cor. of T32S R6W.
A Willow 4" dia., bears N.56°W., 4 lks. dist.
A Pine 40" dia., bears N.10°E., 51 lks. dist.

W.H. Byars, under contract # 420 survey dated Sept. 16, 1881 (DCSO records Vol. 20 Page(s) 8701)

I begin at the Standard cor. to Tps. 32 S., Ranges 6 and 7 West, Post gone, set new post, viz; An Ash 48" long, 4" sq., 18" for standard cor. mkd. S C T32S on N., R6W S31 on E., R7W S36 on W. and 6 notches on E. N. and W. faces, from which
A Pine 48" dia., bears N.10°E., 51 lks. dist.
A Willow 5" dia., bears N.56°W., 4 lks. dist.
The same being old witness trees.

BLM resurvey by John Jelley, Rollin Aanrud, Lynn Roseberry, Cadastral Surveyors, under Group #'s 350 & 688, surveyed May 1969/March 1970 (DCSO records Vol. 35 Page(s) 14469)

Point for the standard cor. of Tsp. 32 S., Rs. 6 & 7 W., at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established.

Survey by Ronald Brandt L.S. #841 - For: Ronald & Linda Brandt - July 1979 - M 78-48

Set 1" x 30" Iron rod, flush, from which
3" dwarf Apple bears S.66°30'E., 4.41 ft.
4" Peach bears S.82°W., 14.50 ft. measured to trunk centers, not marked.
Fenceline 25 ft. north. An 1855 closing corner reset using single proportion measure.

Found OK by R. Wytcherley, Feb. 2001 - M136-55
Fd. 1" IR BC by R. Brandt 10/2018 C.S. File 65/98-11