

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; and 6 of T32-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8634)

Set ¼ sec. post, from which
A Y.Pine 40" dia., bears N.89°W., 47 lks. dist.
A Laurel 6" dia., bears N.80°E., 30 lks. dist.

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1861 (DCSO records Vol. 20 Page(s) 8662)

(40.00 chs.)
Set a Laurel post, 4 ft. long, 4" sq., 18" in the ground, mkd. ¼ S on W. side for the ¼ sec. cor., from which
A Laurel 16" dia., bears S.80°E., 17 lks. dist. mkd. ¼ S BT.
A Pine 4" dia., bears West, 32 lks. dist. mkd. ¼ S BT.
(43.70 chs.)
Old ¼ sec. cor. destroyed same and witness trees.

Survey by Howard Johnstone - For: Roseburg Lumber - Feb. 1969
M 33-49

Found - Orig. Bearing trees.
Set 1" x 30" Iron pipe.
Scribed -5" D.Fir N.88½°E., 26.7 ft.
5" D.Fir N.81°W., 42.7 ft.

Survey by Mark Smalley - For: Roseburg Resources Co. - Oct. 1994 - M 121-6

Found - 1" Iron pipe.
7" Fir, N.81°W., 42.7 ft., healed.
6" Fir, N.88½°E., 26.7 ft., healed.
24" Laurel S.80°E., 11.2 ft., rotten center. OBT.
43" Pine, West 21.1 ft., snag. OBT.
Scribed -11" Fir S.15°E., 18.2 ft. "¼ S BT".