

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 972050

PRIMARY CORNER DESCRIPTION Cor. #3 Hoosier & Cor. #4 Brownbear MS

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Mineral survey by W.F. Briggs, US Dep. Mineral Surveyor, under instructions dated Dec. 22, 1899 - (DCSO records Vol. 28 Page(s) 11887)

-----  
A laurel post, 4½ ft. long, 4" sq., set 18" in the ground with stone mound alongside, scribed C3 & 4 MS 383; whence  
    A Laurel, 10" dia., bears S.18°45'E., 76 ft. blazed & scribed C 3 MS 383 BT.  
    A Laurel, 8" dia., bears N.71°E., 44 ft., blazed & scribed C 4 MS 383 BT.

Loren Van Swearingen - Oct. 1961 - M 21-61

-----  
Found - Orig. BT 16" laurel S.18°45'E., 76.0'  
Corner monumented with 5/8"x30" drill steel.

Bruce Shaner - For: Roseburg Resources - March 2002 - M137-35 & C.S. File 65/42-38

-----  
Found - Drill steel, from which a:  
    28" Madrone, OBT, old face, bears S.18¾°E., 72.8 ft. (rec. 76.0 ft.)  
    28" Madrone, OBT, old face, bears N.71°E., 42.0 ft. (rec. 44 ft.)  
New - 6 ft. steel fence post bears West 0.5 ft.