

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 972060

PRIMARY CORNER DESCRIPTION Cor. #3 Buck & Cor. #4 Hoosier MS

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Mineral survey by W.F. Briggs, US Dep. Mineral Surveyor, under instructions dated Dec. 22, 1899 - (DCSO records Vol. 28 Page(s) 11886)

-----  
A laurel post, 4½ ft. long, 4" sq., set 18" in the ground with stone mound alongside, scribed C3 & 4 MS 383; whence  
    A Laurel, 10" dia., bears S.62°E., 7 ft. blazed & scribed C 3 MS 383 BT.  
    A Laurel, 6" dia., bears N.82°E., 17 ft., blazed & scribed C 4 MS 383 BT.

Loren Van Swearingen - Oct. 1961 - M 21-61

-----  
Found - Orig. BT 14" Laurel S.62°E., 7', scribing visible but in poor condition.  
Scribed- 6" Fir, S.67°30'W., 10.0'  
          4" Fir, S.10°10'E., 13.1  
Corner monumented with 5/8"x30" drill steel.

Bruce Shaner - For: Roseburg Resources - March 2002 - M137-35 & C.S. File 65/42-36

-----  
Found - Drill steel from which a:  
        20" Madrone, orig. BT, old face, bears S.36°E., (V.S. rec. = S.62°E.) 7.0 ft.  
        12" D.Fir BT, face overgrown, bears S.67½°W., 10.8 ft.  
        10" D.Fir BT, face overgrown, bears S.10°E., 13.1 ft.  
New - 6 ft. steel fence post bears S.30°W., 1.0 ft.