

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 972130

PRIMARY CORNER DESCRIPTION Cor. #2 Gold Standard & Cor #1 Buck MS

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Mineral survey by W.F. Briggs, US Dep. Mineral Surveyor, under instructions dated Dec. 22, 1899 - (DCSO records Vol. 28 Page(s) 11884)

-----  
A laurel post, 4½ ft. long, 4" sq., set 18" in the ground with stone mound alongside, scribed C2 & 1 MS 383; whence  
    A pine, 20" dia., bears S.86½°W., 101 ft., blazed & scribed C 2 MS 383 BT.  
    A laurel, 10" dia., bears North 23 ft., blazed & scribed C 1 MS 383 BT.

Loren Van Swearingen - Oct. 1961 - M 21-61

-----  
Both orig. BTs remain; the Pine has blown over.  
Corner monumented with 5/8"x30" drill steel.

Bruce Shaner - For: Roseburg Resources - March 2002 - M137-35 & C.S. File 65/42-33

-----  
Found - Drill steel in mound of rock, from which a:  
    20" Pine BT, orig. BT, now blown down & rotten, bears S.86½°W., 101 ft.  
    12" Madrone BT, scribes visible bears S.41°W. 7.3 ft  
    12" Madrone BT, scribes visible bears N.50°E. 6.6 ft  
    (No record of Madrone BTs)