

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 972140

PRIMARY CORNER DESCRIPTION Cor. #2 Buck & Cor. #1 Hoosier MS

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Mineral survey by W.F. Briggs, US Dep. Mineral Surveyor, under instructions dated Dec. 22, 1899 - (DCSO records Vol. 28 Page(s) 11885-6)

A laurel post, 4½ ft. long, 4" sq., set 18" in the ground with stone mound alongside, scribed C2 & 1 MS 383; whence
 An alder, 18" dia., bears N.81°W., 51 ft., blazed & scribed C2 MS 383 BT.
 A laurel, 6" dia., bears N.26°E., 15 ft. blazed & scribed C1 MS 383 BT.

Loren Van Swearingen - Oct. 1961 - M 21-61

Orig. 10" Laurel N.26°E. is in; orig. mound of stones also in.
Corner monumented with 5/8"x30" drill steel.

Bruce Shaner - For: Roseburg Resources - March 2002 - M137-35 & C.S. File 65/42-35

Found - Drill steel in mound of stone, from which a:
 10" Madrone BT, now snag, face rotted out, bears N.18°E., (rec. N.26°E.) 15.0 ft. (Shows tag & axe marks)
New BTs- 18" D.Fir BT, I scribed "MCBT" bears N.1°W. 10.0 ft.
 14" D.Fir BT, I scribed "MCBT" bears N.65°E. 16.6 ft
 6 ft. steel fence post bears South, 0.5 ft.