

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 972150

PRIMARY CORNER DESCRIPTION Cor. #2 Hoosier & Cor. #1 Brownbear MS

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Mineral survey by W.F. Briggs, US Dep. Mineral Surveyor, under instructions dated Dec. 22, 1899 - (DCSO records Vol. 28 Page(s) 11886-7)

A laurel post, 4½ ft. long, 4" sq., set 18" in the ground with stone mound alongside, scribed C2 & 1 MS 383; whence
 A Fir, 6" dia., bears S.52°W., 37 ft., blazed & scribed C 2 MS 383 BT.
 A Pine, 10" dia., bears N.24°E., 42 ft., blazed & scribed C 1 MS 383 BT.

Loren Van Swearingen - Oct. 1961 - M 21-61

Found corner, which was monumented.

Bruce Shaner - For: Roseburg Resources - March 2002 - M137-35 & C.S. File 65/42-37

Found - 1" iron pipe in mound of stone, from which a:
 26" D.Fir, OBT, face overgrown, bears S.52°W., 37.7 ft.
 28" Pine, OBT, scribe visible, bears N.24°E., 43.0 ft. (rec. 42 ft.)
New - ft. steel fence post bears S.30°W., 1.0 ft.