

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 100201

PRIMARY CORNER DESCRIPTION Cor. for Secs. 25 & 36 only, T32-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8839)

Set an iron post 3 ft. long, 2" dia., 24" in the ground for cor. of secs. 25 and 36, with brass cap mkd.

T32S
S25
S36
R9W
1917

from which

A Fir 36" dia., bears S.40°W., 65 lks. dist. mkd. T32S R9W S36 BT.

A Laurel 14" dia., bears N.15°W., 78 lks. dist. mkd. T32S R9W S25 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 1967 - C.S. File 54/44-29

Found - 36" now 40" D.Fir S.40°W., 42.9 ft., shows good scar
14" Laurel, now dead stob, N.15°W., 51.5 ft., scribe visible.

GLO brass cap, properly mkd., 1917.

New BT - 8" D.Fir N.47°W., 19.0 ft. mkd. T32S R9W S25 CS BT.