

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19 only (West)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8777)

Set a Fir post 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 13, 18, 19, and 24, mkd. T32S R8W S18 on NE.; S19 on SE.; R9W S24 on SW.; and S13 on NW.; also 3 notches on the N. and S. edges of same and from which
A Fir 40" dia., bears N.4°E., 298 lks. dist. mkd. T32S R8W S18 BT.
A Fir 12" dia., bears S.58°E., 115 lks. dist. mkd. T32S R8W S19 BT.
A Sugar Pine 28" dia., bears S.58°W., 58 lks. dist. mkd. T32S R9W S24 BT.
A Fir 15" dia., bears N.52°W., 224 lks. dist. mkd. T32S R9W S13 BT.

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8843)

Intersect at the old cor. of secs. 13, 18, 19 and 24, which is a decayed and partly burned post, witnessed as described by the surveyor general. I change this cor. to refer to secs. 18 and 19 only and perpetuate it as follows: alongside the old cor.
Set an iron post 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 18 and 19, T32S R8W only, with brass cap marked
T32S
S18
S19
R8W
1917
from which
A Fir 5" dia., bears N.54°E., 75 lks. dist. mkd. T32S R8W S18 BT. (New BT)
A Fir 18" dia., bears S.55°E., 115 lks. dist. mkd. T32S R8W S19 BT. (Old BT)