

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 31 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8773)

Set a stone 12x12x8 ins., 8" in the ground for the ¼ sec. cor. marked SC ¼ on N. face, from which

A Fir 24" dia., bears S.36°W., 21 lks. dist. mkd. SC ¼ S BT.

A Fir 24" dia., bears N.20°W., 36 lks. dist. mkd. SC ¼ S BT.

BLM Resurvey by Norman D. Price, U.S. Surveyor, Under instructions dated Sept. 22, 1916 - (DCSO records Vol. 21 Page(s) 8859)

The standard ¼ cor. of sec. 31, which is a granite stone 12x8x4 ins. above ground, firmly set, mkd. and witnessed as described by the surveyor general. Obliterate markings on bearing tree referring to sec. South of line and take new bearing tree as follows:

A Fir 15" dia., bears N.41°E., 59 lks. dist. mkd. SC ¼ S31 BT.