

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8822)

Set a Fir post, 3 ft. long, 3" sq., 20" in the ground and marked ¼ S on W side for ¼ sec. cor., and from which
A fir, 36" dia., bears N.80°W., 23 lks., mkd: ¼ S BT.
A fir, 22" dia., bears S.50°E., 72 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - April/May 1968 - C.S. File 54/65-46

Found - 36 D.Fir, now 25' Stob, N.80°W., 15,2 ft., old axe work.
22", now 36" D.Fir, S.50°E., 47.5 ft., old axe work no scribing, however, both trees are approximate size and good bear. & dist.
Also call at creek of 1 ch. south hits very good. Old scribed post at corner point not of record. This corner also used since 1944, forest location tag.
Set Brass Cap at Cor. Mkd: County Surveyors T32S R8W
Office, 1968 S 31|S 32
New BT - 12" D.Fir N.63°W., 11.8 ft. mkd."¼ S31 CS BT"
Reblazed & rescribed -
36" D.Fir S.50°E., 47.5 ft. mkd. ¼ S32 CS BT.

BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #2004, survey March/Oct. 2002- (DCSO records Vol. 54 Page(s) 21101)

The ¼ sec. cor. of secs. 31 and 32, perpetuated and recorded by the Douglas County Surveyors Office in 1968; monumented with an iron post, 1½" dia., firmly set, projecting 8" above the ground, with brass cap (properly) mkd. from which the remaining original bearing tree
A fir, 34" dia., bears S.50°E., 49.3 ft., with healed blaze. (Record, 47.5 ft.)
and a BT mkd. by the Douglas County Surveyors Office
A fir, 18" dia., bears N.62½°W., 12.1 ft., with healed double blaze.

DCSO-GIS Corner visitation - 1/30/2004 - Typed: 2/10/2011 - C.S. File 67/33-1

Monument - 1¼" IP/BC Comment - ok