

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474 dated May 10, 1883 - (DCSO recs Vol 21 Pg 8822)  
-----  
Set a fir post 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 29, 30, 31, & 32. Marked T32S R8W S29 on NE, S32 on SE, S31 on SW, and S30 on the NW faces also one notch on S and five notches on E angles of same, from which  
A fir, 7" dia. bears N.28°E., 43 lks. mkd: T32S R8W S29 BT  
A fir, 14" dia. bears S.64°E., 10 lks mkd: T32S R8W S32 BT  
A sugar pine, 24" dia., bears S.44°W., 36 lks., mkd: T32S R8W S31 BT.  
A fir, 6" dia. bears N.58°W., 53 lks. mkd: T32S R8W S30 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - May 1968 - C.S. File 54/65-16  
-----  
Found - Orig. BTs: 14" now 36" D.Fir S.64°E., 6.6 ft., faint bark scribe "T R8W S BT"  
24" Pine, gone, stump hole, S.44°W., 23.8 ft.  
7" D.Fir now snag, N.28°E., 28.4 ft., shows scar.  
No trace of NW orig. BT  
Set - Brass cap at cor. mkd: County Surveyors T32S R8W  
Office S 30|S 29  
1968 S 31|S 32  
New BTs- 10" Yew N.59°E., 5.8 ft., mkd: T32S R8W S29 CS BT.  
11" Yew N.4½°W., 4.0 ft., mkd: T32S R8W S30 CS BT.  
24" D.Fir S.56½°W., 69.2 ft. mkd: T32S R8W S31 CS BT  
Reblazed & rescribed -  
36" D.Fir S.64°E., 6.6 ft., mkd: T32S R8W S32 CS BT.

Douglas Co. Surveyors Office - A. Vic Cangie - Jim Cook & Karen Cheney - Aug. 31, 1976 - C.S. File 59/18-29  
-----  
Found - A 1968 brass cap uprooted in root wad. Entire area has slid & all but the 1968 Fir, (24", S.56½°W., 62.9 ft., now 32" dia.) are down.  
Found no trace of 24" Pine. (1968)  
Set - A witness corner that bears N.37°W., 89.3 ft., with a brass cap stamped: DOUGLAS CO. SURVEYOR 1976  
WITNESS CORNER  
S 30|S 29  
S 31|S 32  
T32S R8W  
New BTs- A 10" D.Fir bears S.2°W., 15.4 ft., mkd: "X" & "BT" in a double blaze.  
An 11" chinquapin, bears N.2°W., 41.0 ft. mkd: "X" & "BT" in a double blaze.

continued next page

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An 18" D.Fir bears N.53°E., 8.0' marked "X" and "BT" in a double blaze. - (added 4/20/2016)

---

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - Oct. 22, 1992 - C.S. File 64/32-16

-----

Found - 1976 2½" DCSO brass cap on a 1½" O.D. Iron pipe protruding 8" above ground. 1976  
 Un-monumented corner position in slide, is determined at record bearing and distance (S.37°E., 89.3 ft.) from 1976 BC/IP. A check of brg. and dist. to 34" dia. D.Fir BT from 1968 is made and checks well with record (S.56½°W., 69.2 ft.) in 1968 visit. The dist. 62.9 ft. in 1976 visit is probably a transposed number problem. The proper distance of 69.2 ft. appears to have been used in 1976 corner renewing field work.

Found - 10" now 13" dia. D.Fir with a fully healed double blaze bears S.2°W., 15.4 ft. (agrees w/rec.) 1976  
 11" Chinquapin now root hole, bears N.2°W., 41.0 ft. (agrees w/rec)  
 18" now 19" dia. D.Fir with a fully healed double blaze, bears N.50°E., 7.3 ft. (Rec. N.53°E., 8.0 ft.) BT not typed in 1976, found in field notes of corner renewal in CS. 59/18(-29)

New BTs- 34" dia. D.Fir w/a fully healed double blaze facing NE BT scribed in 1968 bears south, 108.8 ft  
 11" dia. madrone bark scribed "WC T32S R8W S30 CS BT" bears N.17°W., 42.3 ft.

---

BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #2004, survey March/Oct. 2002- (DCSO records Vol. 54 Page(s) 21101-3)

-----

The cor. of secs. 29, 30, 31, & 32, perpetuated from original evidence no longer in existence, as determined at record distance from the remaining bearing tree mkd. by the Douglas County Surveyors Office in 1968, and a witness corner established by the Douglas County Surveyors Office in 1976, from which the bearing tree and witness corner

A fir, 34" dia., bears S.55¼°W., 69.2 ft., with healed blaze

An iron post, hereinafter described, bears N.38¾°W. 89.3 ft

At the corner point  
 Set a stainless steel post, 28" long, 2½" dia., 27" in the ground, with brass cap mkd.

T32S	R8W
S 30	S 29
S 31	S 32

2002

continued next pg

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which new bearing trees  
A yew, 13" dia., bears N.65¼°E., 15.8 ft., mkd. T32S R8W S29 BT.

A yew, 8" dia. bears N.82°E., 17.1 ft mkd. T32S R8W S32 BT  
No suitable tree available in the SE. quadrant.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this point, the witness cor. established by the Douglas County Surveyors Office in 1976, bears N.38°40'16"W., 89.30 ft., monumented with an iron post, 1½" dia., firmly set, projecting 8" above the ground, with brass cap mkd.

DOUGLAS COUNTY SURVEYOR

WITNESS CORNER

S 30 | S 29

S 31 | S 32

T32S R8W

S.37°E. 89.3 FT

1976

from which the remaining bearing trees mkd. by the Douglas County Surveyors Office, in 1976

A fir, 20" dia., bears N.50½°E., 7.3 ft., with healed double blaze. (This tree was inadvertently omitted from 1976 county renewal but was included in the 1992 renewal record.)

A fir, 15" dia., bears S.1½°W., 15.4 ft., with healed double blaze.

and a BT mkd. by the Douglas County Surveyors Office, in 1992

A madrone, 13" dia., bears N.16¾°W., 42.9 ft., with scribe marks CS BT visible on the bark.

Fd 2002 BLM BC& Accessories per rec. 11/2018 - T Hostetter, M175-12