TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8824)

Set a fir post 3 ft long, 3" sq., 20" in the ground marked ¼S on W side for the ¼ sec. cor., from which
A fir, 13" dia., bears N.69°E., 46 lks., mkd: ¼ S BT.
A fir, 36" dia., bears S.27°W., 40 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - May 1968 - C.S. File 54/65-15

Found - 13", now 24" D.Fir, N.69°E., 30.4 ft., bark scribe visible "¼S".
36" D.Fir, now snag, S.27°W., 26.4 ft., faint bark scribe "¼".
Set Brass Cap at Cor. Mkd: County Surveyors Office 1968 T32S R8W ¼ S 30|S 29
New BT - 42" D.Fir S.49°W., 42.0 ft. mkd. ¼ S30 CS BT.
Reblazed & Rescribed -
24" D.Fir N.69°E., 30.4 ft. mkd. ¼ S29 CS BT.

Tony Hostetter - For: Weyerhaeuser Co. - Nov. 2018 - M175-12

Found - 1968 DCSO brass cap as described C.S. File 54/65-15. From which:
28" Fir, scribing visible, bears; N.69°E., 30.4 FT.
46" Fir, face evident BT tag, bears S.49°W., 42.0 FT
34" Fir, face evident BT tag, bears N.69°E., 30.4 FT