

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8830)

A laurel, 8" dia., which I mark T32S R8W S8 on NE, S17 on SE, S18 on SW, and S7 on NW faces also 4 notches on the S and 5 notches on the E angles of same for the cor. to secs. 7, 8, 17, & 18 from which

- A chinquapin, 8" dia., bears N.50°E., 7 lks., mkd: T32S R8W S8 BT.
- A chinquapin, 8" dia., bears S.5°E., 10 lks., mkd: T32S R8W S17 BT.
- A laurel, 10" dia., bears S.15°W., 7 lks., mkd: T32S R8W S18 BT.
- A chinquapin, 8" dia., bears N.10°W., 23 lks., mkd: T32S R8W S7 BT.

Milner L. Larson - June 1956 - C.S. File 42/169 & M3-5

Could not find any trace of corner after intensive search, so set corner by double proportionate measurement.
Set 1/2" iron pipe corner, scribed new BTs
8" madrone, N.62°00'E., 0.7(?) ft.
8" madrone, S.39°30'E., 4.2 ft.
18" fir, S.10°00'W., 25.4 ft.
10" madrone, N.24°00'W., 12.4 ft.

Fd. Ok by DCSO, JP - 4/19/1967, C.S. File 54/65-