

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8832)

Set a laurel post, 3 ft. long, 3" sq., 20" in the ground marked $\frac{1}{4}$ S on the W side for the $\frac{1}{4}$ sec. cor., and from which
A laurel, 10" dia., bears S.15°E., 24 lks., mkd: $\frac{1}{4}$ S BT.
A chinquapin, 8" dia., bears S.40°W., 8 lks., mkd: $\frac{1}{4}$ S BT.

Milner L. Larson - June 1956 - C.S. File 42/169 & M3-5

Orig. corner could not be found.
Set 1/2" iron pipe at proportionate measurement.
Scribed 2 new trees:
8" madrone, N.66°30'W., 19.5 ft.
20" madrone, N.64°30'E., 19.1 ft.

Ron Quimby - For: Plum Creek Timber Co. - 4/2016 - M171-9

Found - 3/4" iron rod (1/2" iron pipe)
19" madrone N.66 $\frac{1}{2}$ °W., 19.5' fully healed blaze
23" madrone S.64 $\frac{1}{2}$ °E., 19.1' partially open scribe (N.64°30'E.)
New - 6" madrone S.45°W., 10.1' scribed " $\frac{1}{4}$ S7 BT"
8" chinquapin S.49°E., 11.6' scribed " $\frac{1}{4}$ S8 BT"