

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8833)

-----  
Set a stone 16x12x8", 12" in the ground marked with 5 notches on the S & E angles of same for the cor. to secs. 5, 6, 7, & 8, and from which  
A laurel, 8" dia., bears N.85°E., 32 lks., mkd: T32S R8W S5 BT.  
A laurel, 6" dia., bears S.26°E., 21 lks., mkd: T32S R8W S8 BT.  
A fir, 30" dia. bears S.40°W., 31 lks. mkd: T32S R8W S7 BT  
A fir, 50" dia. bears N.25°W., 14 lks. mkd: T32S R8W S6 BT

Douglas Co. Surveyors Office - John M. Powell - May 1968 - C.S. File 54/65-76

-----  
Reported as not found  
1<sup>st</sup> report  
Found good blaze lines east & west. But no trace of corner. It has been logged & brunt.  
2<sup>nd</sup> report  
2<sup>nd</sup> time looked for, ran line from 6|5 south, good line control for dist. calls of 7 chains & 6 chains S & E. Area old logging & snags, many old brushed lines in area.

BLM dependent resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Group #821 & 876, surveyed July 1973/July 1975 - (DCSO records Vol. 40 Page(s) 15996-7)

-----  
The cor. of secs. 5, 6, 7, & 8, monumented with the original basalt stone, 16x12x8", firmly set, projecting 10", above ground, with 2 grooves on E face, from which the remains of the original bearing trees:  
A madrone root crown, size indeterminate, bears N.85°E., 32 lks.  
A fir, 35" dia., bears S.40°W., 31 lks., with illegible scribe marks visible on burned bark blaze.  
A fir stump, size indeterminate, bears N.25°W., 14 lks., no marks visible.  
At the corner point  
Set an iron post, 28" long. 2½" dia., 24" in the ground, with brass cap mkd.  
T32S R8W  
S 6|S 5  
S 7|S 8  
1975  
from which new bearing trees

continued next page

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A fir, 7" dia. bears N.58°E., 81 lks. mkd. T32S R8W S5 BT  
A madrone, 6" dia., bears S.49°E., 21 lks., mkd. T32S R8W  
S8 BT.  
A fir, 6" dia. bears N.15½°W., 29 lks. mkd. T32S R8W S6 BT  
Deposit corner stone alongside iron post.