

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8823)

Set a stone 12x12x8", 8" in the ground mkd. ¼ on N face for ¼ sec. cor., from which
A fir, 15" dia., bears S.63°E., 20 lks., mkd: ¼ S BT.
A fir, 14" dia., bears N.54°W., 22 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - May/June 1968 - C.S. File 54/65-73

Found - Corner Stone mkd. "¼"
15", now 20" D.Fir, S.63°E., 13.2 ft., bark scribe visible, "¼ T"
14", now 16" D.Fir, N.54°W., 14.5 ft., bark scribe visible, "¼ B"

Set Brass Cap at Cor. Mkd: County Surveyors T32S R8W
Office 1968 ¼ S 29
S 32

Reblazed & Rescribed -
20" D.Fir S.63°E., 13.2 ft. mkd. ¼ S32 CS BT.
16" D.Fir N.54°W., 14.5 ft. mkd. ¼ S29 CS BT.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 4/1/1993 - C.S. File 64/41-17

Found - 2½" dia. brass cap on a 1½" O.D. iron pipe, protruding 12" above ground. 1968
Fd broken stone around base of brass cap with iron pipe, largest stone measures 8"x8"x5". No marks found. (Orig. stone).
15" now 24" dia. 4½' high double trunked D.Fir stump with a partially healed single blaze "¼ S32 CS BT" on easterly trunk, root crown bears S.63°E., 13.2' (agrees with rec.) Orig. BT
14" now 21" dia. 3½' high D.Fir stump with a partially healed double blaze "¼ S29 CS BT" bears N.57°W., 13.9' (rec. N.54°W., 14.5') orig. BT.
No bark scribing found on BTs. Marks possibly removed when rescribed in 1968
New BTs- 4" D.Fir double blazed & scribed "X BT" S.6°E., 27.8 ft.
10" D.Fir, double blazed and scribed "¼ S 29 CS BT" bears N.44½°E., 51.9 ft