

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond Dickerson Deputy Surveyor under contract #474 dated May 10, 1883 - (DCSO recs Vol 21 Pg 8825-6)

-----  
Set a stone 16x12x10", 10" in the ground marked ¼S on N side for the ¼ sec. cor., from which

A laurel, 6" dia., bears North, 50 lks., mkd: ¼ S BT.

A laurel, 7" dia., bears S.36°E., 16 lks., mkd: ¼ S BT.

-----  
Douglas Co Surveyors Office - John Powell - 5/1968 - CS 54/65-27

-----  
Reported as not found.

Found: E-W brushed line at approx. ¼ cor. N-S ribbon line.

2 small laurel's 6"-7" for trees. Not found.

-----  
Gordon L. Caster, Medford Dist. BLM, Preliminary Administration survey for Forest Management Purposes - Dated Sept. 1979 & filed Oct. 1, 1987 - M104-70

-----  
Set ¼ cor. mkd. ref. trees: Madrone 10" brs. N.34¼°E., 15.2' - D.Fir 6" dia., brs. S.89°W., 25.9'

Per letter from Terry Nickerson, Medford BLM dated 9/25/1987: "This is not a Cadastral Survey, was not done under the direction of a cadastral survey or Registered Land Surveyor. It was surveyed using Theodolite & EDM with a closure, but the BLM can not stand behind it." Terry N.

-----  
Douglas Co. Surveyors Office - John M. Powell - Randy Smith - March 16, 1982 - C.S. File 61/30-17

-----  
Found - 5/8" iron rod set by G.Caster, BLM Cadastral Surveyor  
Note - "In a phone conversation between myself and Gordon Caster (BLM Surveyor from Medford dist.) I was told that the 5/8" I.R. was set at midpoint on the section line in conjunction with an administrative survey and that it is not an official cor." (signed) Gregory Quibell, Douglas Co. Surveyors Office.

Found - 7" D.Fir bears S.89°W., 26.0 ft., tagged not scribed  
10" madrone bears N.36°E. 15.2 ft tagged not scribed

Note - "As in 1968, I found no evidence of orig. corner".  
(signed) John M. Powell.

New - PK nail in 11" Madrone bears S.34°E., 68.5 ft.  
5/8" Iron rod with plastic cap bears S.34°E. 55.7 ft  
PK nail in 34" D.Fir bears S.67°E., 45.0 ft.  
5/8" Iron rod with plastic cap bears S.67°E. 35.8 ft

This point (¼ cor.) to be destroyed by new road.

¼ corner located at approx. P line station PL 36+30.