

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8812)

Set a fir post, 3 ft. long, 3" sq., 20" in the ground marked ¼ S on W side for ¼ sec. cor. from which
 A fir, 36" dia., bears S.64°E., 46 lks., mkd: ¼ S BT.
 A pine, 30" dia., bears N.78°W., 34 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - May 1968 - C.S. File 54/65-64

Reported as not found.
Found pine with axed ¼ opened tree with no results.
Also fir stump rotten. Both trees hit fair for bearing & dist., however no evidence to renew said cor.

Robert M Thompson, LS#1358 - For: Boise Cascade Timber Lands of Oregon - Oct. 21, 1983 - M 95-33 & C.S. 58/275(N)

Set - 5/8" I. Rod with yellow cap mkd: "Thompson PLS 1358"
New - Scribed the following BTs "¼ S1358 BT"
 7" chinquapin, N.65½°W., 15.9 ft.
 3" chinquapin, S.44°W., 13.3 ft., with "X BT" scribing.
Note- Corner is on a brushy spur ridge, slopes N'ly.

1