

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8814)

Set a stone 14x12x8", 10" in the ground for the ¼ sec. cor. marked ¼ S on W side, from which
A fir, 6" dia., bears S.74°E., 15 lks., mkd: ¼ S BT.
A laurel, 6" dia., bears West, 55 lks., mkd: ¼ S BT

Douglas Co. Surveyors Office - John M. Powell - May 1968 - C.S. File 54/65-27

Reported as not found.
Squared stake at approx. ¼ cor. All possible trees cut into, good N-S line to cadastral brass cap, both sides of line clear cut.

Robert M Thompson, LS#1358 - For: Boise Cascade Timber Lands of Oregon - Oct. 21, 1983 - M 95-33 & C.S. 58/275-3(N)

Set - 5/8x30" I. Rod with yellow cap mk. "THOMPSON PLS 1358"
New - Scribed the following BTs "¼ S(#) 1358 BT"
9" madrone, S.25½°E., 12.7 ft.
10" D.Fir N.71½°W., 41.2 ft.
Note- Corner is 830 ft. N of Rd. #32-7-19.3 no N. side of main ridge, easterly.

Ron Quimby - Crew: N. Fromdahl, D. Manring, R. Olsen - 10/2014 - C.S. File 65/86-29

Found - 5/8" I. Rod
12" Madrone S.25°E., 12.7 legible scribes.
16" D.Fir N.71°W., 41.2 good scar.
New - A 6" Fir S.23°W., 3.3 ft. scribed ¼ S29 BT.
A 6" Fir N.58°E., 1.5 ft. scribed ¼ S28 BT.
Note - Area burnt 8/2013
Compass decl. 15½°E.