

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8816)

Set a Laurel post 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 16, 17, 20, & 21. mkd T328 R8W S16 on NE, S21 on SE, S20 on SW, and S17 on NW faces also 3 notches on the S and 4 notches on the E angles of same, from which
A sugar pine, 20" dia., bears N.30°E., 20 lks., mkd: T32S R8W S16 BT.
A fir, 16" dia., bears S.67°E., 12 lks., mkd: T32S R8W S21 BT.
A laurel, 6" dia., bears S.2°W., 19 lks., mkd: T32S R8W S20 BT.
A fir, 30" dia., bears N.54°W., 22 lks., mkd: T32S R8W S17 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - April 1968 - C.S. File 54/65-39

Found - Orig. 16" now 28" D.Fir S.67°E., 7.9 ft., faint scribe visible.
Orig. 30" now 42" D.Fir N.54°W., 14.5 ft., bark scribe visible.
Orig. 6" laurel now down, S.2°W., 12.5 ft., scribe found "S", & other marks.
No trace of NE BT (Hole)
Set brass cap at cor. mkd: COUNTY SURVEYORS T32S R8W
OFFICE S 17 | S 16
1968 S 20 | S 21

Reblazed & rescribed -
28" D.Fir S.67°E., 7.9 ft., mkd: T32S R8W S21 CS BT.
42" D.Fir N.54°W., 14.5 ft. mkd: T32S R8W S17 CS BT.
New BTs- 8" maple S.30°W., 19.4 ft., mkd: T32S R8W S20 CS BT.
39" D.Fir N.4°E., 33.6 ft. mkd: T32S R8W S16 CS BT.