

| Alias | Description |
|-------|-------------|
|       |             |
|       |             |
|       |             |
|       |             |

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8817)

- 
- A fir, 24" dia., which I marked T32S R8W S9 on NE, S16 on SE, S17 on SW, & S8 on NW also four notches on the S & E angles of same for the cor. to secs. 8, 9, 16, & 17, from which
    - A laurel, 4" dia., bears N.45°E., 45 lks., mkd: T32S R8W S9 BT.
    - A laurel, 8" dia., bears S.10°E., 38 lks., mkd: T32S R8W S16 BT.
    - A sugar pine, 36" dia., bears S.65°W., 25 lks., mkd: T32S R8W S17 BT.
    - A laurel, 8" dia., bears N.11°W., 30 lks., mkd: T32S R8W S8 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - May/June 1968 - C.S. File 54/65-75

- 
- Found - Orig. 24" D.Fir corner tree, now stump, scribing visible, "S" "3" & other faint marks.  
36" Pine, now snag, S.65°W., 16.5 ft., no marks visible.  
No trace of 3 small laurel BTs.  
Set brass cap on side of corner tree stump mkd:  
County Surveyors  
T32S R8W  
S 8 | S 9  
S 17 | S 16  
Office 1968
- New BTs- 7" Tan Oak N.32°E., 41.6 ft. mkd: T32S R8W S9 CS BT.  
13" D.Fir N.69½°W., 31.2 ft. mkd: T32S R8W S8 CS BT.  
30" D.Fir S.36°W., 64.0 ft mkd: T32S R8W S17 CS BT.  
No trees in SW quad (Old Unit)

Bruce Shaner - For: Superior Lumber - June 30, 1994 - M120-31 & C.S. File 63/154-8

- 
- Found - 24" D.Fir corner tree, now 36" stump with old scribes "S & 3" visible.  
36" Sugar Pine BT, now a snag, no scribes visible, badly rotted, bears S.60°W., 18.3 ft. (rec. S.65°W., 16.5 ft. must have been to face.)  
10" Tan Oak BT, face overgrown, bears N.38°E., 43.6 ft. (rec. N.32°E., 41.6 ft.)  
18" D.Fir BT, face overgrown, bears N.65½°W., 28.5 ft. (rec. N.69½°W., 31.2 ft.)
- continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

34" D.Fir BT, face overgrown, bears S.40°W., 62.0 ft. (rec. S.36°W., 64.0 ft.)  
DCSO Brass Cap, (2½" dia. on a 1" I.P.) bears N.80°E., 3.2 ft. (I added "BO. 1" to this)  
No BTs available in SE Quadrant.  
Set - 5/8"x30" Iron Rod with 1½" aluminum cap marked "Shaner Engineering RLS 430" in center of stump.  
Note - All BT's marked by County Surveyor in 1968 were measured to brass cap, not center of corner tree. Corner is 200 yds. easterly of end of old logging road in Sec. 8.

Richard Templin - For: Fruit Growers Supply 3/2002 - M139-74  
-----  
Found 5/8" iron rod as reported on 1994 corner renewal  
Previous renewal states that the "corner is 200 yards easterly from end of old logging road in sec. 8." This should state that corner lies 200 ft. Southerly from old logging road. (See previous ren. for corner info.)

BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #2004, survey March/Oct. 2002- (DCSO records Vol. 54 Page(s) 21096-7)  
-----  
The cor. of secs. 8, 9, 16, and 17, perpetuated and recorded by Bruce Shaner, in 1994; monumented with an iron rod, 5/8" dia., firmly set, projecting 8" above the top of a sawed fir stump, with aluminum cap mkd. SHANER ENGR RLS 430; this is the original cor. tree, now 60" dia., from which the remains of an original bearing tree  
A sugar pine snag, 36" dia., bears S.60°W., 18.3 ft., no marks visible on badly decayed, open blaze. (Record, S.65°W., 16.5 ft.)  
From this point, a point established as a witness point by the Douglas County Surveyors Office, in 1968, bears N.80°00'E. 3.2 ft.; monumented with an iron post, 1½" dia., firmly set, projecting 8" above the ground, with brass cap mkd. T32S R8W S8 S9 S17 S16 1968, from which bearing trees mkd by the County Surveyor's Office  
A tan oak, 10" dia., bears N.34¼°E., 41.3 ft., with healed blaze.  
A fir, 38" dia., bears S.38°W., 63.5 ft., with healed blaze.  
A fir, 23" dia., bears N.69°W., 28.1 ft., with healed blaze.