

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8819)

A fir, 10" dia., which I mkd T32S R8W S4 on NE, S9 on SE, S8 on SW, & S5 on NW faces also five notches on the South, and four notches on the E angles of the same for the cor. to secs. 4, 5, 8, & 9 and from which
A fir, 50" dia. bears N.37°E., 45 lks. mkd: T32S R8W S4 BT
A fir, 48" dia. bears S.65°E., 22 lks. mkd: T32S R8W S9 BT
A fir, 40" dia. bears S.34°W., 38 lks. mkd: T32S R8W S8 BT
A fir, 20" dia. bears N.54°W., 23 lks. mkd: T32S R8W S5 BT

Douglas Co. Surveyors Office - James Byron, Deputy - M. Godfrey & S.A. Bilow - Aug. 1958 - C.S. File 49/110

Found - Orig. 48" now 42" R.Fir S.65°E., 14.5 ft. Good bark scribing "T32S"
Now 24" R.Fir that checks bearing & dist. for Orig. NW BT.
Note - This corner & all BTs are in fill slope of road. I uncover fill material to find scribing.
Find 1" drill steel at corner.
I do not set brass cap.
New BTs- I rescribe (bark):
42" R.Fir S.65°E., 14.5 ft., S9 T32S R8W CS BT.
24" R.Fir N.54°W. 16.2 ft. Scribed S5 T32S R8W CS BT
36" R.Fir N.58°E. 27.8 ft. scribed S4 T32S R8W CS BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - April 1968 - C.S. File 54/65-31

Found - 1" drill steel at sec. cor.
42" D.Fir now stob, S.65°E., 14.5 ft., bark scribed T32S R8W S9 CS BT.
36" D.fir, now 36" N.58°E., 27.8 ft scribing visible
24" now 25" D.Fir N.54°W., 16.2 ft scribing visible "T32S R8W S5 CS BT"
New BT - 40" D.Fir S.10°E., 73.7 ft., mkd: T32S R8W S9 CS BT
No other trees available.
Note - This corner lies 50.0 ft., west of West Fork Creek Road.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM dependent resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Group #821 & 876, surveyed July 1973/July 1975 - (DCSO records Vol. 40 Page(s) 15993)

The cor. of secs. 4, 5, 8, & 9, determined at record distance from the remains of the original BTs:

A fir snag, 42" dia., bears S.57°E., 22 lks., no original marks visible. This tree was rescribed by Byron, in 1958, and has scribe marks T32S R8W S9 CS BT visible on bark blaze. (Record, S.65°E.)

A fir snag, 25" dia., bears N.54°W., 23 lks., no original marks visible. This tree was rescribed by Byron, in 1958, and has scribe marks R8W S5 CS visible on partially healed blaze.

and a BT mkd. by Byron, Deputy County Surveyor, in 1958


A fir, 42" dia., bears N.55½°E., 42 lks., with healed blaze.

and the remains of a BT mkd. by Powell in 1967

A sawed fir stump, 40" dia., bears S.8°E., 113 lks., no marks visible.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.



from which a new bearing tree

A fir, 10" dia., bears S.26¼°W., 142 lks., mkd. T32S R8W S8 BT.

No suitable tree available within limits in SE quadrant.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy Surveyor - Ed Monrean - Sept. 24, 1992 - C.S. File 64/32-5

Found - 1975 BLM brass cap on an iron pipe 4" below ground. Orig. SE BT is down, shattered remains of a stump left.

1958 renewal, NE BT is down.

All other BTs fd as in 1975 BLM dependent resurvey & 1968 renewal.

New BT - 11" dia., D.Fir double blazed & scribed "T32S R8W S9 CS BT" bears S.2°E., 56.2 ft.

Note - Corner is approx. 50 ft., west of a paved road.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #2004, survey March/Oct. 2002 - (DCSO records Vol. 54 Page(s) 21098-9)

The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2½" dia., firmly set, projecting 1 in. above the ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees
A fir stump, size indeterminate, bears S.57°E., 14.5 ft., no marks.

A fir snag, 32" dia., bears N.54°W., 15.2 ft., with healed blaze.

and the remains of a bearing mkd. by the Douglas Co Surveyors Office, in 1958, and reported by Roseberry and Aanrad

A fir snag, size indeterminate, bears N.55½°E., 27.7 ft., with healed double blaze.

and the remains of a bearing mkd. by the Douglas County Surveyors Office, in 1967, and reported by Roseberry and Aanrud

A sawed fir stump, size indeterminate, bears S.8°E., 74.6 ft., no marks visible.

and a bearing tree mkd. by Roseberry and Aanrud
A fir, 20" dia., bears S.26¼°W., 93.7 ft., with healed blaze.

and a bearing mkd by the Douglas Co Surveyors Office, in 1992
A fir, 15" dia., bears S.2°E., 56.2 ft., with healed blaze.

The geographic position (NAD 1983 (98)) of the cor. of secs. 4, 5, 8, and 9, as determined by a tie to National Geodetic Survey station N 748, is as follows:

Latitude: 42°48'38.96"N. Longitude: 123°39'39.94"W.

Fd. Ok by R. Quimby - 3/2002 - M139-64 A&B

Ron Quimby - For: Plum Creek Timber Co. - 4/2016 - M171-9

Found - Brass cap per July 1973/July 1975 BLM Dependent resurvey group # 821 & 876
Rotten fir stump (size indeterminate) S.57°E., 14.5'
No marks
33" Fir snag N.54°W., 15.2' healed blaze
Downed fir snag (size indeterminate) N.55½°E., 27.7'
Healed double blazes w/tag
Fir stump (size indeterminate) S.08°E., 74.6' no marks visible
24" Fir S.26¼°W., 93.7' healed blaze
20" Fir S.02°E., 56.2' healed blaze