

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 33 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8772)

Set a post 3 ft. long, 3" sq., 18" in the ground for a ¼ sec. cor. marked ¼ S SC, from which a
 Fir 24" dia., bears N.18°W., 48 lks. dist. mkd. SC ¼ S BT.
 Sugar Pine 46" dia., bears S.34°W., 246 lks. dist. mkd. SC ¼ S BT.

BLM Resurvey by Norman D. Price, U.S. Surveyor, Under instructions dated Sept. 22, 1916 - (DCSO records Vol. 21 Page(s) 8856)

Find no evidence of the cor. post established for standard ¼ cor. of sec. 33. True point for cor. established from original bearing trees.
 At exact cor. point
 Set a porphyry stone 15x10x6 ins., 10" in the ground, for standard ¼ cor., marked SC ¼ on N. face.
 The old bearing trees being dead, I obliterate markings on same and take new bearing trees as follows:
 A Fir 20" dia., bears N.36°E., 344 lks. dist. mkd. SC ¼ S33 BT.
 A Fir 24" dia., bears N.52°W., 141 lks. dist. mkd. SC ¼ S33 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - May 1968 - C.S. File 54/65-58

Found - Corner stone 15x10x6 mkd. "¼".
 20" now 36" D.Fir, N.36°E., 227.0 ft., shows good scar.
 24" now 26" D.Fir N.52°W., 93.1 ft. open and show scribing "¼".

Set Brass cap at cor. mkd: County Surveyors Office
 T 32 S R
 Doug. Co. ¼ S 33 8
 Josp. Co. ¼ T 33 S W
 1968

New BT - 5" Tan Oak N.68½°E., 8.7 ft. mkd. S33 CS BT. There were no other BTs in range for scribing. Top of spur bears West 162.0 ft.