

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8816-7)

Set a stone 14x12x8, 10" in the ground for the ¼ sec. cor. marked ¼ on N side, from which
A fir, 24" dia., bears North, 46 lks., mkd: ¼ S BT.
A fir, 22" dia., bears S.10°E., 6 lks., mkd: ¼ S BT.

Milner L. Larson, PE #3642 - Aug. 31, 1955 - C.S. File 42/16

Set corner marker from old BT.

Lorne Swearingen - For: The Robert Dollar Co. - Wit: R.A. Harris & M Larson - May 20, 1960 - C.S. file 51/63-6

Found in poor condition: The orig. stone for the corner was gone but both orig. BTs remain. The called distances & bearing would not fit to set the corner unless the orig. distances to the North BT was used as a slope distance.

Set a 1" (ID) iron pipe for the corner.
Although the orig. BT S.10°E., 6 lks., distance is a stump with bark scribing visible, the bark is very loose and orig. evidence will be lost in the near future, so I scribed a new 12" Fir, S.19°W., 24.9 ft. distance & mkd. S21¼S BT
The North BT still has a very little bark scribing visible, but it may be gone in a few years so I rescribed orig. BT in the wood as follows: A 28"fir North 24.9 ft., (orig. called for 30.4' but I used this as slope distance) scribed S16¼S 4186 BT.

Ron Quimby - For: Plum Creek Timber Co. - June 2014 - M168-12

Found - 1" iron pipe together with the following BTs:
40" Fir with healed scar bears N, 26.7 ft.
24" Fir with healed scar bears S.20°W., 24.5 ft.
New BTs- 7" Fir scribed ¼ S16 BT bears N.15°E., 20.9 ft.
12" Fir scribed ¼ S21 BT bears S.29°E., 27.5 ft.