

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 340540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #2004, survey March/Oct. 2002- (DCSO records Vol. 54 Page(s) 21103)

Point for the center ¼ sec. of cor. of sec. 9, at intersection with the E. and W. center line.
Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd. T 32 S R 8 W
C 1/4 S 9
2002

from which
A fir, 19" dia., bears N.10°E., 28.1 ft., mkd. C ¼ S9 BT.
A fir, 18" dia., bears S.81½°W., 41.8 ft., mkd. C ¼ S9 BT.
Deposit a magnet in a white plastic case at the base of the stainless steel post.

Ron Quimby - Crew: N. Fromdahl, R. Olsen & D. Manring - 11/20/2014 - C.S. File 65/86-34

Found - Brass cap (properly mkd)
20" Fir N.10°E., 28.1 ft. good scar.
20" Fir S.81°W., 41.8 ft. good scar.
New - 30" Fir, N.19°W., 18.7 ft. scribed C¼ S9 BT
7" Tan Oak S.53°E., 26.2 ft. scribed C¼ S9 BT
Note - Lat & Long hand held GPS
N 42°48.235
W 123°39.085
Compass decl. 15½°E.