

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Standard Cor. for Secs. 33 & 34 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - R.W. Smith; S.J. Flause, crew - April 24, 1985 - C.S. File 62/25-8

Found - 11x12x10 in. stone (1916 rec. 16x12x7) with 3 grooves on E. and W. faces sitting on ground surface with NE. corner of stone checking BT references as shown.

DCSO brass cap out of ground.

Orig. BT, 24" now 32" D.Fir with faint evidence of healed blaze, bears N.69°E., 36.5 ft. (Rec. N.68°E., 35.0 ft.)

Orig. BT, 34" now 40" D.Fir, faint bark scribe visible S.26°W., 7.3 ft.

Orig. BT, 16" now 25" D.Fir with healed reblaze, bears N.42°W., 13.9 ft. (Rec. N.48°W.)

1968 BT, 9" now 10" Madrone with partially healed double blaze, bears N.10°E., 35.7 ft.

The 1968 DCSO brass cap and I.P. (1" x 30") is RESET at corner in mound of stone and earth, with 1916 resurvey stone buried along SW. edge. "RESET 1985" is added to cap, top of cap is flush with mound. NOTE: top of cap is set at position determined and referenced for corner. Due to bedrock the monument cannot be set vertically. Bottom of monument is situated N.69°E., 0.4 ft. from vertical.

No new accessories added. (Sketch in CS File)