TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8803-4)

Set a stone 16x14x12", 10" in the ground marked with 1 notch on S and 3 notches on the East angles of same for cor. to secs. 27, 28, 33, & 34, and from which

A fir, 14" dia. bears N.54°E., 38 lks mkd: T32S R8W S27 BT
A chinquapin, 4" dia., bears S.45°E., 6 lks., mkd: T32S R8W S34 BT.
A fir, 15" dia. bears S.61°W., 61 lks mkd: T32S R8W S33 BT
A fir, 12" dia. bears N.58°W., 40 lks mkd: T32S R8W S28 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - April/May 1968 - C.S. File 54/65

Found - 16x24x12 Stone at corner, 3 notches on E-1 on the S
Orig. 14", now 20" D.Fir, N.54°E. 25.1 ft.(slope) bark scribe faint.
Orig. 4", now 8" Chinquapin, S.45°E., 4.0 ft., shows Scar.
Orig. 15",now 31" D.Fir, S.61°W., 40.3 ft., scribe visible "W".
Orig. 12" D.Fir, now stump, N.58°W. 26.4 ft.

Set Brass Cap at Cor. mkd: County Surveyors Office 1968

T32S	R8W
S 28	S 27
S 33	S 34

Reblazed & Rescribed -
31" D.Fir S.61°W. 40.3 ft. Mkd. T32S R8W S33 CS BT
20" D.Fir N.54°E. 22.6 ft. mkd. T32S R8W S27 CS BT
New BT - 19" Cedar N.78°W. 12.7 ft. mkd. T32S R8W S28 CS BT

DCSO-GIS Corner visitation - 2/3/2004 - Typed: 2/10/2011 - C.S. File 67/33-1

Monument - 1¼" IP/BC Comment - ok