

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8805)

-----  
A Chinquapin, 6" dia., which I mark T32S R8W S22 on NE, S27 on SE, S28 on SW, and S21 on NW faces, also 2 notches on the S and three notches on the E angle of same for the corner to secs. 21, 22, 27 and 28, and from which

A Laurel, 8" dia, bears N.70°E. 97 lks mkd T32S R8W S22 BT  
A Fir, 8" dia., bears S.60°E., 15 lks. mkd T32S R8W S27 BT  
A Laurel, 8" dia. bears S.60°W. 80 lks mkd T32S R8W S28 BT  
A Pine, 12" dia. bears N.14°W. 50 lks. mkd T32S R8W S21 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - May 1968 - C.S. File 54/65-24

-----  
Found - 8", now 16" D.Fir, S.60°E. 9.9 ft. This tree had been opened but buried in fill of road. Dug out to find part of "BT". All other trees gone from road construction.

Set - Brass Cap at Cor. mkd: County Surveyors T32S R8W  
Office S 21 | S 22  
1968 S 28 | S 27

New BTs- 12" Laurel S.35°W. 62.0 ft. Mkd. T32S R8W S28 CS BT.  
28" D.Fir N.28°W., 42.6 ft. mkd. T32S R8W S21 CS BT.  
10" Laurel N.7°E., 58.5 ft. Mcd. T32S R8W S22 CS BT.

Reblazed & Rescribed -

16" D.Fir S.60°E., 9.9 ft. mkd. T32S R8W S27 CS BT.

Note - This corner lies approx. 60 ft. west of road.

DCSO-GIS Corner visitation - 1/29/2004 - Typed: 2/10/2011 - C.S. File 67/33-1

-----  
Monument - 1¼" IP/BC Comment - ok

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 5/20/2025 - C.S. File 67/60-36

-----  
Found - 2½" D.C.S.O. Brass cap proj. 8"  
48" D.Fir N.28°W. 42.6ft fully healed single blaze.  
18" Laurel N.7°E. 58.5ft fully healed single blaze.  
29" D.Fir S.60°E. 9.5ft (Rec 9.9) fully healed single blaze. Add 3½" mag nail right side center.  
New - 13" D.Fir S.47°W. 14.0ft scribed T32S R8W S28 CS BT on double blaze. 3½" mag nail set left side center.

Continued next page

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor Secs 21, 22, 27, & 28

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Notes - Mon is approx. 60ft west of road on steep N.W. slope  
Compass decl.  $14\frac{1}{2}^{\circ}$ E.  
OGRS COORDINATE SYSTEM  
COTTAGE GROVE-CANYONVILLE ZONE  
N. 23782.282 E. 81706.445