

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8807)

-----  
A laurel 5" dia., which I marked T32S R8W S15 on NE, S22 on SE, S21 on SW & S16 on NW faces also tree notches on E & S angles of same for the cor. to secs. 15, 16, 21, & 22, from which

- A chinquapin, 6" dia., bears N.30°E., 46 lks., mkd: T32S R8W S15 BT.
- A laurel, 6" dia., bears S.1°E., 24 lks., mkd: T32S R8W S22 BT.
- A laurel, 6" dia., bears S.68°W., 14 lks., mkd: T32S R8W S21 BT.
- A laurel, 6" dia., bears N.52°W., 25 lks., mkd: T32S R8W S16 BT.

Milner L. Larson, PE #3642 - Aug. 31, 1955 - C.S. File 42/16

-----  
Corner set by proportionate measurement.  
At point for corner set a 1½" by 36" iron pipe for corner marker  
Marked four trees:  
A 13" Madrone bears N.61°25'W., 27.4 ft.  
A 5" Madrone bears S.56°08'W., 28.3 ft.  
An 11" Live Oak bears N.75°39'E. 45.9 ft.  
A 13" madrone bears S.8°17'E., 40.0 ft.

Fd. Ok by DCSO, JMP, 4/1968 - C.S. File 54/65  
Fd. Ok by DCSO, 10/1992 - C.S. File 64/39-2

Ron Quimby - For: Plum Creek Timber Co. - June 2014 - M168-12

-----  
Found - 1½" iron pipe, together with the following BTs:  
16" Live Oak with healed blaze bears N.76°E. 45.9 ft  
8" Madrone with healed blaze bears S.56°W., 28.3 ft  
18" Madrone with healed blaze bears N.61°W., 27.4 ft  
New BT - 11" Chinquapin scribed ¼ S22 BT" bears, S.18°E., 19.7 ft.