

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8808)</p> <p>-----</p> <p>Set a laurel post, 4 ft. long, 3" sq., 20" in the ground, marked ¼ S on W side for ¼ sec. cor., from which</p> <p> A fir, 6" dia., bears N.18°E., 10 lks., mkd: ¼ S BT.</p> <p> A fir, 8" dia., bears S.14°W., 20 lks., mkd: ¼ S BT.</p>
<p>Milner L. Larson, PE #3642 - Aug. 31, 1955 - C.S. File 42/16</p> <p>-----</p> <p>At the point for the corner a cross is made on the bedrock for the marker. (By proportionate measurement) Point falls on the south side of Bear Creek.</p> <p>Marked two trees:</p> <p> A 10" maple, N.16°49'W., 36.3 ft.</p> <p> A 30" D.Fir, N.70°19'E., 28.4 ft.</p>
<p>Douglas Co. Surveyors Office - John Powell - April 1968 - C.S. File 54/65-6</p> <p>-----</p> <p>Reported as not found.</p> <p>Cor. lies in Creek, high water and logs have taken out BTs.</p>
<p>Ron Quimby - For: Plum Creek Timber Co. - June 2014 - M168-12</p> <p>-----</p> <p>Set - PK nail n bedrock at ¼ corner.</p> <p> 5/8" iron rod with aluminum cap mkd "I.E. ENGINEERING" as reference to true corner 35.00 ft. south on line. Together with the following BTs (references are from actual corner)</p> <p> An 6" Fir scribed "¼ S15 BT" bears N.73°E., 28.1 ft.</p> <p> An 8" alder scribed "¼ S16 BT" bears S.58°W., 5.5 ft.</p> <p> An 8" alder scribed "¼ S16 BT" bears N.78°W., 26.8 ft.</p>
<p> </p>