

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8808)

Set a stone 14x12x12" marked with 4 notches on the S and 3 notches on the E, for the cor. to secs. 9, 10, 15, & 16, from which

- A laurel, 10" dia., bears N.35°E., 55 lks., mkd: T32S R8W S10 BT.
- A laurel, 6" dia., bears S.62°E., 68 lks., mkd: T32S R8W S15 BT.
- A fir, 24" dia., bears S.28°W., 52 lks., mkd: T32S R8W S16 BT.
- A laurel, 6" dia., bears N.53°W., 50 lks., mkd: T32S R8W S9 BT.

Milner L. Larson, PE #3642 - Aug. 31, 1955 - C.S. File 42/16

Set corner marker from Old BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - April 1968 - C.S. File 54/65

Found - Orig. 6" laurel stob, N.53°W., 33.0 ft. no scribing.
Orig. 24" now 40" D.Fir S.28°W., 34.3 ft., faint bark scribe "R8WBT"
No trace of other BTs nor stone.

Set brass cap at cor. mkd: County Surveyors T32S R8W
Office S 9 | S 10
1968 S 16 | S 15

New BTs- 8" Laurel N.53°W., 28.8 ft., mkd. T32S R8W S9 CS BT.
8" Pine N.88°E., 35.7 ft. mkd. T32S R8W S10 CS BT.
5" Pine, East 33.0 ft., S15 CS BT.

Reblazed & rescribed -
40" D.Fir S.28°W., 34.3 ft., T32S R8W S16 CS BT.

Bruce Shaner - For: Superior Lumber - June 30, 1994 - C.S. file 63/154-7 & M120-31

Found - 2½" DCSO Brass cap on a 1" Galv. I.P.
40" D.Fir BT, scribes visible, bears S.28°W. 34.3 ft
10" Madrone BT, face overgrown, bears N.53°W., 27.8 ft. (rec. 28.8 ft.)
5" Pine BT, bears East, 33.0 ft. now gone.

New - 6" D.Fir, bears S.51°E., 11.4 ft. scribed "S15 T32S R8W BT"

Note - Corner lies 500 ft. above & westerly of U.S.

Cont.

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #2004, survey March/Oct. 2002- (DCSO records Vol. 54 Page(s) 21093-4)

The cor. of secs. 9, 10, 15, and 16, perpetuated and recorded by Larson, in 1955, subsequently perpetuated by the Douglas County Surveyors Office in 1968, and rehabilitated and recorded by Shaner, in 1994, monumented with an iron post, 1" dia., firmly set, projecting 12" above the ground, with brass cap (properly) mkd.

from which an original bearing tree

A fir, 40" dia., bears S.27°W., 34.3 ft., with healed blaze. (Record, S.28°W.)

and the remains of BTs mkd. by the Douglas County Surveyor

A sugar pine, 19" dia., bears N.87°E., 34.0 ft., with healed blaze.

An uprooted madrone, size indeterminate, bears N.54½°W., 26.4 ft., no marks visible.

and a bearing tree mkd. by Shaner

A fir, 6" dia., bears S.56°E., 11.3 ft., with healed blaze.

and a new bearing tree

A fir, 6" dia. bears N.71¾°W. 16.2 ft. mkd. T32S R8W S9 BT

Fd. Ok by D. Edwards, 8/2005 - M148-31

Fd. BC & 4 BTs by R. Quimby 6/2014 - M168-12