

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8811)

A fir, 14" dia., which I marked $\frac{1}{4}$ S on W side for the $\frac{1}{4}$ sec. cor., from which
 A pine, 72" dia., bears S.25°E., 25 lks., mkd: $\frac{1}{4}$ S BT.
 A fir, 8" dia., bears West, 12 lks., mkd: $\frac{1}{4}$ S BT

Douglas Co. Surveyors Office - John M. Powell - 3/27/1968 - C.S. File 54/65

Reported as not found.
Found - Large 72" pine down area, burnt.
 No other BTs
Also found -
 10" laurel N.53°W., 26.0 ft., scribed $\frac{1}{4}$ S BT 3571.
 8" laurel S.59°W., 14.5 (or possibly 74.5) scribed $\frac{1}{4}$ S 3571.
These bearings & dist. are found by just facing up trees approx.

BLM dependent resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Group #821 & 876, surveyed July 1973/July 1975 - (DCSO records Vol. 40 Page(s) 15992)

Point for the $\frac{1}{4}$ sec. cor., of secs. 3 and 4, at proportionate dist; there is no remaining evidence of the original corner. Set an iron post, 28" long, 2 $\frac{1}{2}$ " dia., 24" in the ground, with brass cap mkd.

T32S R8W
 $\frac{1}{4}$
S 4 | S 3
1975

from which
 A fir, 18" dia., bears S.3°E., 55 lks., mkd. $\frac{1}{4}$ S3 BT.
 A fir, 18" dia., bears S.82°W., 68 $\frac{1}{2}$ lks., mkd. $\frac{1}{4}$ S4 BT.

Ron Quimby - For: Rsbg Resources Co - 3/2002 - M139-64 A&B

Found - BLM brass cap, properly marked.
 27" Fir S.3°E, 36.3 ft.
 18" Fir (stump) S.82°W, 45.2 ft.
NEW BTs- 12" Madrone N.83°E, 10.3 ft. (Scribed 1/4 S3 BT)
 16" Madrone S.22°W, 20.0 ft. (Scribed 1/4 S3 BT)