

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO rec Vol 21 Pg 8810)

-----  
A fir, 20' dia., which I marked ¼ S on N side, for the ¼ sec. cor., from which

A fir, 10" dia., bears N.30°E., 10 lks., mkd: ¼ S BT.

A fir, 24" dia., bears S.40°E., 21 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell & crew - 3/26/1970 - C.S. File 54/65-21

-----  
Found - 20" D.Fir corner tree, now down, faint bark scribed "S /"

Orig. 10" D.Fir, now stob, N.30°E., 6.6 ft., faint scribe "BT"

Orig. 24" D.Fir, now stump, S.40°E., 13.9 ft., no scribe visible.

Set brass cap at cor. mkd: COUNTY SURVEYORS T32S R8W

OFFICE ¼ S 3  
1970 S 10

New BTs- 30" D.Fir, N.78°E., 13.0 ft., scribe visible "¼ S3 CS BT"

4" D.Fir, S.69°W., 15.8 ft., scribed "CS BT"

No other trees available to the south

This corner lies approx. 300 ft. east of ravine.

BLM dependent resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Group #821 & 876, surveyed July 1973/July 1975 - (DCSO records Vol. 40 Page(s) 15990-1)

-----  
The ¼ sec. cor., of secs. 3 & 10, perpetuated and recorded by Powell, in 1970, monumented with an iron pipe. 1" dia., with brass cap, firmly set in a root hole, projecting 6" above ground, alongside of which is lying the original corner tree, a fir, 26" dia., with scribe marks ¼ S visible on opened blaze. The brass cap is (properly) mkd.

from which the remains of the original bearing trees

A fir snag, 17" dia., bears N.30°E., 10 lks., with scribe marks ST visible on bark blaze.

A sawed fir stump, 36" dia., bears S.40°E., 21 lks., with illegible scribe marks visible on bark blaze.

and the remains of bearing trees mkd. by Powell

A fir snag, 35" dia., bears N.75°E., 19 lks., with scribe marks ¼ S3 CS BT visible on opened blaze.

A fir, 5" dia., bears S.67½°W., 23½ lks. with healed blaze and a new bearing tree

A fir, 6" dia., bears N.5½°E., 73½ lks., mkd. ¼ S3 BT.

cont. TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Mark Smalley - For: Roseburg Forest Products - 7/18/2003 - M 143-2

-----  
Found - DCSO brass cap on an iron pipe.  
17" Fir snag, N.30°E., 6.6' (Orig)  
29" Fir snag, N.78°E., 13.0' scribe vis.  
15" Fir S.69°W., 15.8' healed.  
New - 5" Fir S.14°E., 5.2' scribed "¼S BT"  
5" Fir S.45°W., 9.1' scribed "¼S BT"

Fd. Ok by D. Edwards, 8/2005 - M148-31

BLM resurvey by Brandon G Courtright, Cadastral Surveyor, under Group No. 2754, surveyed May/July 2014 - (DCSO records, Vol. 58 page(s) 23373-4)

-----  
The ¼ sec. cor. of secs. 3 & 10, perpetuated by Powell, in 1970, and further perpetuated by Smalley, in 2003, monumented with an iron post, 1½" dia., firmly set, projecting 8" above ground, with a brass cap (properly) mkd. from which the remains of an original bearing tree  
A charred fir snag, size indeterminate, bears N.30°E., 6.6 ft., no marks visible.  
and the remains of the bearing trees mkd. by Powell, reported by Roseberry and Aanrud in 1973-75  
A charred fir snag, size indeterminate, bears N.75°E., 12.5 ft., no marks visible.  
A fir, 16" dia., bears S.67½°W., 15.5 ft., with a healed blaze.  
and a bearing tree mkd. by Roseberry and Aanrud in 1973-75  
A fir, 24" dia., bears N.5½°E., 49.5 ft., with a healed blaze.  
and the remains of the bearing trees mkd. by Smalley  
A charred fir snag, 6" dia., bears S.14°E., 5.2 ft., with a healed blaze and a washer in the face.  
A charred fir snag, 6" dia., bears S.45°W., 9.1 ft., with a healed blaze and a washer in the face.  
The geographic position in NAD 1983 (2011)  
Latitude: 42°48'39.53"N. Longitude: 123°37'55.32"W.