TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 3; and 34, T31-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 19 Page(s) 8099)

Set a Fir post 3 ft. long, 3" sq., 20" in the ground mkd. ¼ S on the N. side for the ¼ sec. cor., from which
A Fir 44" dia., bears S.2°E., 60 lks. dist. mkd. ¼ S BT
A Fir 7" dia., bears N.20°W., 30 lks. dist. mkd. ¼ S BT

Douglas Co. Surveyors Office - John M. Powell, and crew - Jan. 1967 - C.S. File 54/36-74

Found - 44" now 50" D.Fir S.2°E., 39.6 ft., faint "BT" visible, also notch below main face.
No trace of 7" Fir, N.20°W., 19.8ft.
Iron pipe at ¼ corner, Unrecorded.
Tree with face but no scribing at N.10°E., 16.1 ft.

Set Brass cap at cor. mkd: County Surveyors Office
(Set alongside I.Pipe) T 31 S R 8 W
¼ S 34 / S 3
1967

New BTs- 10" D.Fir S.37°E., 18.4 ft. mkd. ¼ S3 CS BT.
10" D.Fir N.10°E., 16.1 ft. mkd. ¼ S34 CS BT.

As in original notes, spring branch 132.0 ft. E. of ¼ Corner