

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 476100

PRIMARY CORNER DESCRIPTION C.C. for Secs. 2 & 3 only, T33-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Norman D. Price, U.S. Surveyor, under Group #33, surveyed July/Oct. 1919 - C.S. File 64/76-1

At point of intersection (4.47 chs., West from the standard cor. of secs. 34 and 35), At point of intersection, Set a diorite stone 16x10x6 ins., 11" in the ground, for closing cor. of secs. 2 and 3, mkd. CC on S.; with 2 grooves on E. and 4 grooves on W. face;; from which

A Fir 36" dia., bears S.18°E., 28 lks. dist. mkd. T33S R8W S2 CC BT.

A Madrona 14" dia., bears S.40¼°W., 90 lks. dist., mkd. T33S R8W S3 CC BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - May 1968 - C.S. file 54/65-14

Found - Stone, no marks visible.
14" Laurel S.40½°W., 59.4 ft., shows good scar.
36" D.Fir, now snag, S.18°E., 18.5 ft., scribe visible, not legible.

Set Brass cap at cor. mkd: County Surveyors Office
T 32 S R 8 W

Doug. Co. CC S 34
Jos. Co. S 3 | S 2
T 33 S

New BTs- 7" D.Fir S.8°W., 14.6 ft. mkd. T33S R8W S3 CC CSBT
7" D.Fir S.71°W., 17.5 ft. mkd. T33S R8W S3 CC CSBT
No trees to SE.

Corner lies approx. 295 ft. W. of sec. Cor. to 34|35 only.
Also, about 80 ft. S. of small ravine.