

PRIMARY CORNER DESCRIPTION Standard cor. for Secs. 34 & 35 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8770)

Set a stone 14x12x10 ins., 10" in the ground for the standard cor. to secs.34 and 35, marked S C on N.; 2 notches on E.; and 4 on W. sides of same, from which

- A Fir 12" dia., bears N.24°E., 28 lks. dist. mkd. SC T32S R8W S35 BT.
- A Fir 26" dia., bears S.54°E., 13 lks. dist. mkd. SC T33S R8W S2 BT.
- A Fir 15" dia., bears N.45°W., 63 lks. dist. mkd. SC T32S R8W S34 BT.

BLM Resurvey by Norman D. Price, U.S. Surveyor, Under instructions dated Sept. 22, 1916 - (DCSO records Vol. 21 Page(s) 8854)

The standard cor., which is a granite stone 12x10x4 ins., above ground, firmly set, marked as described by the surveyor general, from which the old bearing trees bear as follows:

- A Fir 15" dia., bears N.24°E., 28 lks. dist. mkd. SC T32S R8W S35 BT.
- A Fir 18" dia., bears N.45°W., 63 lks. dist. mkd. SC T32S R8W S34 BT.

I obliterate markings on bearing tree referring to sec. 2.

Douglas Co. Surveyors Office - John M. Powell, and crew - May 1968 - C.S. File 54/65

Found - 12x10x4 stone "SC" mkd. on N. face.
 15" now 17" D.Fir N.24°E., 18.5 ft., shows good scar.
 18" now D.Fir stump, N.45°W., 41.6 ft., scribe visible "BT".

Set Brass cap at cor. mkd: County Surveyors Office

	T 32 S	R
Doug. Co.	<u>S 34</u> <u>S 35</u>	8
Josp. Co.	S 2	W

1968

New BT - 14" D.Fir N.77°W., 33.1 ft. mkd. T32S R8W S34 SC CS BT.
 Corner lies approx. 50.0 ft. N. of small ravine.

continued next page

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Standard cor. for Secs. 34 & 35 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Arthur R. Rambo, Cadastral Surveyor under Group No. 2179, surveyed July/Nov. 2007 - (DCSO records, Vol. 55 Page(s) 21614-5)

The standard cor. of secs. 34 & 35, on the S. bdy. of the Tp. perpetuated by the Douglas County Surveyor's Office, in 1968, monumented with an iron post, 1½" dia. firmly set, projecting 17" above the ground, with brass cap (properly) mkd. from which the remains of the original bearing trees

A fir, 17" dia., bears N.19½°E., 18.5 ft., with a healed blaze. (Record, N.24°E.)

A sawed fir stump, 29" dia., bears N.45°W., 38.6 ft., no marks visible. (Record, 41.6 ft.)

and a bearing tree mkd. by the Douglas County Surveyor's Office, in 1968

A fir, 26" dia. bears N.77°W., 33.9 ft with a healed blaze