

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8794)

Set a laurel post, 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 26, 27, 34, & 35. Marked T32S R8W S26 on the NE, S35 on the SE, S34 on the SW and S27 on the NW faces also 1 notch on the S and 2 notches on the East angles of same, and from which

- A laurel, 8" dia., bears N.15°E., 20 lks., mkd: ¼ S26 BT.
- A fir, 6" dia. bears S.44°E., 32 lks. mkd: T32S R8W S35 BT
- A fir, 15" dia. bears S.44°W., 38 lks mkd: T32S R8W S34 BT
- A fir, 36" dia. bears N.50°W., 34 lks mkd: T32S R8W S27 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - April 1968 - C.S. File 54/65-41

Found - 36" now 43" D.Fir N.50°W., 22.4 ft., shows faint but not legible scribe marks.
8" now 12" laurel, center rotten, N.15°E., 13.2 ft.
15" now 32" D.Fir S.36½°W., (Rec. S.44°W.) 25.1 ft., faint scribe visible.
6" now 21" D.Fir S.44°E., 19.7 ft. (Rec. 21.1) no marks visible.

Set brass cap at cor. mkd: County Surveyors Office 1968

T32S	R8W
S 27	S 26
S 34	S 35

Reblazed & rescribed -
43" D.Fir N.50°W., 22.4 ft. mkd. T32S R8W S27 CS BT.
32" D.Fir S.36½°W., 25.1 ft mkd. T32S R8W S34 CS BT
12" Laurel N.15°E., 13.2 ft. mkd. T32S R8W S26 CS BT
21" D.Fir S.44°E., 19.7 ft., mkd. T32S R8W S35 CS BT

BLM Dependent by Arthur R. Rambo, Cadastral Surveyor under Group No. 2179, surveyed July/Nov. 2007 - (DCSO records, Vol. 55 Page(s) 21615-6)

The cor. of secs. 26, 27, 34, and 35, perpetuated by the Douglas County Surveyor's Office, in 1968, monumented with an iron post, 1½" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd. from which the original bearing trees, remarked by the Douglas County Surveyor's Office, in 1968

- A madrone, 13" dia., bears N.11½°E., 14.1 ft., with fragmentary scribe marks visible on partially healed double blaze. (Record, N.15°E., 13.2 ft.)
- A fir, 22" dia., bears S.44°E., 18.8 ft., with a healed double blaze. (Record, 21.1 ft.) continued next page

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 35" dia., bears S.35½°W., 26.2 ft., with a healed double blaze. (Record, S.44°W., 25.1 ft.)

A fir, 42" dia., bears N.50°W., 22.4 ft., with a healed double blaze.

The geographic positions in (NAD 1983 (CORS 96)), as determined by ties to temporary GPS points established using NAVSTAR GPS static data, and the National Geodetic Survey's Online Positioning User Service (OPUS), of the following corners are:

The corner of sections 26, 27, 34, and 35:

Latitude: 42°45'13.69"N. Longitude: 123°37'15.57"W.

Fd. as per rec. by R. Quimby, 2/2014 - M167-22